

Data-driven Natural Language Generation: Paving the Road to Success

Jekaterina Novikova, Ondřej Dušek and Verena Rieser

Interaction Lab

Heriot-Watt University

Edinburgh, EH14 4AS, UK

{j.novikova, o.dusek, v.t.rieser}@hw.ac.uk

Abstract

We argue that there are currently two major bottlenecks to the commercial use of statistical machine learning approaches for natural language generation (NLG): (a) The lack of reliable automatic evaluation metrics for NLG, and (b) The scarcity of high quality in-domain corpora. We address the first problem by thoroughly analysing current evaluation metrics and motivating the need for a new, more reliable metric. The second problem is addressed by presenting a novel framework for developing and evaluating a high quality corpus for NLG training.

1 Evaluation metrics for NLG

Up to 60% of NLG research published between 2012–2015 relies on automatic evaluation measures, such as BLEU (Gkatzia and Mahamood, 2015). The use of such metrics is, however, only sensible if they are known to be sufficiently correlated with human preferences, which is not the case, as we show in the most complete study to date, across metrics, systems, datasets and domains.

We evaluate three end-to-end NLG systems: RNNLG (Wen et al., 2015), TGen (Dušek and Jurčiček, 2015) and LOLS (Lampouras and Vlachos, 2016), using a large number of 21 automated metrics. The metrics are divided into groups of word-based metrics (WBMs, such as TER (Snover et al., 2006), BLEU (Papineni et al., 2002), ROUGE (Lin, 2004), semantic similarity (Han et al., 2013) etc.) and grammar-based metrics (GBMs, such as readability, characters per utterance and per word, syllables per sentence and per word, number of misspellings etc.). To assess the metrics'

Dataset	Lexical richness		Syntactic complexity	
	LS	MSTTR	Level 0-1	Level 6-7
our corpus	0.57	0.75	46%	16%
SFRest	0.43	0.62	47%	13%
SFHot	0.43	0.59	51%	15%
Bagel	0.42	0.41	50%	16%

Table 1: Lexical richness and syntactic variation for the collected corpus and other popular datasets. *LS* measures the proportion of less frequent words in the text, *MSTTR* measures the type-token ratio normalised by the size of the corpus. For D-level complexity, *Level 0-1* include syntactically simple sentences, *Level 6-7* include the most complicated sentences.

reliability, we calculate the Spearman correlation between the metrics and human ratings for the same natural language (NL) utterances, the accuracy of relative rankings and conduct a detailed error analysis.

The results reveal that no metric produces an even moderate correlation with human ratings (max. $\rho = 0.33$), independently of dataset, system, or aspect of human rating. WBMs make two strong assumptions: They treat human-generated NL references as a gold standard which is correct and complete. We argue that these assumptions are very often invalid for corpus-based NLG, especially when using crowdsourced datasets. Grammar-based metrics, on the other hand, do not rely on human-generated references and are not influenced by their quality. However, these metrics can be easily manipulated with grammatically correct and easily readable output that is unrelated to the input. Our study clearly demonstrates the need for more advanced metrics, as used in related fields, e.g. MT (Specia et al., 2010).

2 Corpus development and evaluation

Recent advances in corpus-based NLG (Dušek and Jurčiček, 2015; Wen et al., 2015; Mei et al., 2016; Wen et al., 2016; Dušek and Jurčiček, 2016; Lampouras and Vlachos, 2016) require costly training data, consisting of meaning representations (MRs) paired with corresponding NL texts. In our work, we propose a novel framework for crowdsourcing high quality NLG training data, using automatic quality control measures and evaluating two types of MRs, pictorial and textual, used to elicit data (Novikova and Rieser, 2016).

When collecting corpora for training NLG systems, especially when using crowd workers, the following challenges arise:

- (1) How to ensure the required high quality of the collected data?
- (2) What types of meaning representations can elicit spontaneous, natural and varied data from crowd workers?

To address (1), we filter the crowdsourced data using a combination of automatic and semi-manual validation procedures, as described in (Novikova and Rieser, 2016). We validate the data by selecting native English participants, allowing only well formed English sentences to be submitted, and measuring the semantic similarity of a collected NL utterance and an associated MR. Using this framework, we collected a dataset of 50k instances in the restaurant domain, which is 10 times bigger than datasets currently used for NLG training, e.g. SFRest and SFHot (Wen et al., 2015) or Bagel (Mairesse et al., 2010).

To evaluate the quality of the collected corpus, we analyse the data with regards to lexical richness and syntactic variation and compare our results to other popular datasets in similar domains, i.e. SFRest, SFHot and BAGEL. We use the Lexical Complexity Analyser (Lu, 2012) to measure various dimensions of lexical richness and variation, such as *mean segmental type-token ratio* (MSTTR) and *lexical sophistication* (LS). The results of lexical analysis (see Table 1) show that our corpus is lexically more diverse and as such, considerably more complex. In order to evaluate syntactic variation and complexity of NL references in our corpus, we use the D-Level Analyser (Lu, 2009). Table 1 shows that our collected corpus has the highest proportion of complex sentences (54%

	Logic-based MR	Pictorial MR
informativeness	4.28**	4.51**
naturalness	4.09**	4.43**
phrasing	4.01**	4.40**

Table 2: Human evaluation of the data collected with logic-based and pictorial MRs (** denotes $p < 0.01$)

of sentences scored above level 1). At the same time, the proportion of syntactically complex sentences (levels 6 and 7) is one of the highest.

Furthermore, our dataset requires content selection in 40% of the cases. In contrast to the other datasets, crowd workers were asked to verbalise all the *useful* information from the MR and were allowed to skip an attribute value considered unimportant. As such, learning from this dataset promises more natural, varied and less template-like system utterances.

To address challenge (2) in corpus development, we conduct a principled study regarding the trade-off between semantic expressiveness of the MR and the quality of crowdsourced utterances elicited. In particular, we investigate translating textual MRs (presented in the form of logic-based dialogue acts, such as “inform(name = the Wrestlers, price range = cheap, customer rating = low)”) into pictorial representations as used in, e.g. (Williams and Young, 2007; Black et al., 2011). We show that pictorial MRs result in better quality NLG data than logic-based textual MRs: utterances elicited by pictorial MRs are judged as significantly more natural, more informative, and better phrased, with a significant increase in average quality ratings (around 0.5 points on a 6-point scale), compared to the logical MRs (see Table 2). Pictorial MRs also result in more spontaneous, natural and varied utterances. This is probably due to crowd workers not being primed by lexical tokens. Moreover, as the MR becomes more complex, the benefits of pictorial stimuli increase.

3 Conclusion and future work

Our work addresses two major bottlenecks of current data-driven NLG: Reliable automatic evaluation and efficient high-quality data collection. While our work shows that we can effectively crowdsource data of sufficient quality to train NLG algorithms – in particular, using pictorial representations that reduce bias and elicit more

syntactically varied and lexically rich data – our work also clearly demonstrates the need for more advanced evaluation metrics. We see our work as a first step towards reference-less evaluation for NLG by introducing grammar-based metrics.

Acknowledgements

This research received funding from the EPSRC projects DILiGENT (EP/M005429/1) and MaDRiGAL (EP/N017536/1). The Titan Xp used for this research was donated by the NVIDIA Corporation.

References

- Alan W Black, Susanne Burger, Alistair Conkie, Helen Hastie, Simon Keizer, Oliver Lemon, Nicolas Merigaud, Gabriel Parent, Gabriel Schubiner, Blaise Thomson, Jason D. Williams, Kai Yu, Steve Young, and Maxine Eskenazi. 2011. Spoken dialog challenge 2010: Comparison of live and control test results. In *Proceedings of the SIGDIAL 2011 Conference*. Association for Computational Linguistics, Portland, Oregon, pages 2–7. <http://www.aclweb.org/anthology/W11-2002>.
- Ondřej Dušek and Filip Jurčiček. 2015. Training a natural language generator from unaligned data. In *Proc. of ACL-IJCNLP (Volume 1: Long Papers)*. Beijing, China, pages 451–461. <http://aclweb.org/anthology/P15-1044>.
- Ondřej Dušek and Filip Jurčiček. 2016. Sequence-to-sequence generation for spoken dialogue via deep syntax trees and strings. In *Proc. of ACL*. Berlin, Germany, pages 45–51. arXiv:1606.05491. <http://aclweb.org/anthology/P16-2008>.
- Dimitra Gkatzia and Saad Mahamood. 2015. A snapshot of NLG evaluation practices 2005–2014. In *Proc. of ENLG*. Brighton, UK, pages 57–60. <https://doi.org/10.18653/v1/W15-4708>.
- Lushan Han, Abhay Kashyap, Tim Finin, James Mayfield, and Jonathan Weese. 2013. UMBC_EBIQUITY-CORE: Semantic textual similarity systems. In *Proc. of *SEM*. Atlanta, Georgia, volume 1, pages 44–52. <http://aclweb.org/anthology/S13-1005>.
- Gerasimos Lampouras and Andreas Vlachos. 2016. Imitation learning for language generation from unaligned data. In *Proc. of COLING: Technical Papers*. Osaka, Japan, pages 1101–1112. <http://aclweb.org/anthology/C16-1105>.
- Chin-Yew Lin. 2004. ROUGE: A package for automatic evaluation of summaries. In *Text summarization branches out: Proc. of the ACL-04 workshop*. Barcelona, Spain, pages 74–81. <http://aclweb.org/anthology/W04-1013>.
- Xiaofei Lu. 2009. Automatic measurement of syntactic complexity in child language acquisition. *International Journal of Corpus Linguistics* 14(1):3–28. <http://doi.org/10.1075/ijcl.14.1.02lu>.
- Xiaofei Lu. 2012. The relationship of lexical richness to the quality of esl learners oral narratives. *The Modern Language Journal* 96(2):190–208. http://doi.org/10.1111/j.1540-4781.2011.01232_1.x.
- François Mairesse, Milica Gašić, Filip Jurčiček, Simon Keizer, Blaise Thomson, Kai Yu, and Steve Young. 2010. Phrase-based statistical language generation using graphical models and active learning. In *Proc. of ACL*. Uppsala, Sweden, pages 1552–1561. <http://aclweb.org/anthology/P10-1157>.
- Hongyuan Mei, Mohit Bansal, and Matthew R. Walter. 2016. What to talk about and how? Selective generation using LSTMs with coarse-to-fine alignment. In *Proc. of NAACL-HLT 2016*. San Diego, CA, USA. arXiv:1509.00838. <http://aclweb.org/anthology/N16-1086>.
- Jekaterina Novikova and Verena Rieser. 2016. Crowd-sourcing NLG data: Pictures elicit better data. In *Proc. of the 9th International Natural Language Generation conference (INLG)*. <http://www.aclweb.org/anthology/W/W16/W16-6644.pdf>.
- Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. BLEU: a method for automatic evaluation of machine translation. In *Proc. of ACL*. Philadelphia, PA, USA, pages 311–318. <http://aclweb.org/anthology/P02-1040>.
- Matthew Snover, Bonnie Dorr, Richard Schwartz, Linnea Micciulla, and John Makhoul. 2006. A study of translation edit rate with targeted human annotation. In *Proc. of AMTA*. Cambridge, MA, USA, pages 223–231. <http://mt-archive.info/AMTA-2006-Snover.pdf>.
- Lucia Specia, Dhvaj Raj, and Marco Turchi. 2010. Machine translation evaluation versus quality estimation. *Machine translation* 24(1):39–50. <https://doi.org/10.1007/s10590-010-9077-2>.
- Tsung-Hsien Wen, Milica Gašić, Nikola Mrkšić, Lina Maria Rojas-Barahona, Pei-Hao Su, David Vandyke, and Steve J. Young. 2016. Multi-domain neural network language generation for spoken dialogue systems. In *Proc. of EMNLP-HLT*. San Diego, CA, USA, pages 120–129. arXiv:1603.01232. <http://aclweb.org/anthology/N16-1015>.
- Tsung-Hsien Wen, Milica Gašić, Nikola Mrkšić, Pei-Hao Su, David Vandyke, and Steve Young. 2015. Semantically conditioned LSTM-based natural language generation for spoken dialogue systems. In *Proc. of EMNLP*. Lisbon, Portugal, pages 1711–1721. <http://aclweb.org/anthology/D15-1199>.

Jason D. Williams and Steve Young. 2007. Partially Observable Markov Decision Processes for Spoken Dialog Systems. *Comput. Speech Lang.* 21(2):393–422. <https://doi.org/10.1016/j.csl.2006.06.008>.