

Findings of the E2E NLG Challenge

Ondřej Dušek, Jekaterina Novikova and Verena Rieser

The Interaction Lab, School of Mathematical and Computer Sciences

Heriot-Watt University

Edinburgh, Scotland, UK

{o.dusek, j.novikova, v.t.rieser}@hw.ac.uk

Abstract

This paper summarises the experimental setup and results of the first shared task on end-to-end (E2E) natural language generation (NLG) in spoken dialogue systems. Recent end-to-end generation systems are promising since they reduce the need for data annotation. However, they are currently limited to small, delexicalised datasets. The E2E NLG shared task aims to assess whether these novel approaches can generate better-quality output by learning from a dataset containing higher lexical richness, syntactic complexity and diverse discourse phenomena. We compare 62 systems submitted by 17 institutions, covering a wide range of approaches, including machine learning architectures – with the majority implementing sequence-to-sequence models (seq2seq) – as well as systems based on grammatical rules and templates.

1 Introduction

This paper summarises the first shared task on end-to-end (E2E) natural language generation (NLG) in spoken dialogue systems (SDSs). Shared tasks have become an established way of pushing research boundaries in the field of natural language processing, with NLG benchmarking tasks running since 2007 (Belz and Gatt, 2007). This task is novel in that it poses new challenges for recent end-to-end, data-driven NLG systems for SDSs which jointly learn sentence planning and surface realisation and do not require costly semantic alignment between meaning representations (MRs) and the corresponding natural language reference texts, e.g. (Dušek and Jurčiček, 2015; Wen et al., 2015b; Mei et al.,

2016; Wen et al., 2016; Sharma et al., 2016; Dušek and Jurčiček, 2016a; Lampouras and Vlachos, 2016).¹ So far, end-to-end approaches to NLG are limited to small, delexicalised datasets, e.g. BAGEL (Mairesse et al., 2010), SF Hotels/Restaurants (Wen et al., 2015b), or RoboCup (Chen and Mooney, 2008), whereas the E2E shared task is based on a new crowdsourced dataset of 50k instances in the restaurant domain, which is about 10 times larger and also more complex than previous datasets. For the shared challenge, we received 62 system submissions by 17 institutions from 11 countries, with about 1/3 of these submissions coming from industry. We assess the submitted systems by comparing them to a challenging baseline using automatic as well as human evaluation. We consider this level of participation an unexpected success, which underlines the timeliness of this task.² While there are previous studies comparing a limited number of end-to-end NLG approaches (Novikova et al., 2017a; Wiseman et al., 2017; Gardent et al., 2017), this is the first research to evaluate novel end-to-end generation at scale and using human assessment.

2 The E2E NLG dataset

2.1 Data Collection Procedure

In order to maximise the chances for data-driven end-to-end systems to produce high quality output, we aim to provide training data in high quality and large quantity. To collect data in large enough quantity, we use crowdsourcing with automatic

¹Note that as opposed to the “classical” definition of NLG (Reiter and Dale, 2000; Gatt and Krahmer, 2018), generation for dialogue systems does not involve content selection and its sentence planning stage may be less complex.

²In comparison, the well established Conference in Machine Translation WMT’17 (running since 2006) received submissions from 31 institutions to a total of 8 tasks (Bojar et al., 2017a).

MR	name[The Wrestlers], priceRange[cheap], customerRating[low]
Reference	The wrestlers offers competitive prices, but isn't highly rated by customers.

Figure 1: Example of an MR-reference pair.

Attribute	Data Type	Example value
name	verbatim string	<i>The Eagle, ...</i>
eatType	dictionary	<i>restaurant, pub, ...</i>
familyFriendly	boolean	<i>Yes / No</i>
priceRange	dictionary	<i>cheap, expensive, ...</i>
food	dictionary	<i>French, Italian, ...</i>
near	verbatim string	<i>Zizzi, Cafe Adriatic, ...</i>
area	dictionary	<i>riverside, city center, ...</i>
customerRating	dictionary	<i>1 of 5 (low), 4 of 5 (high), ...</i>

Table 1: Domain ontology of the E2E dataset.

quality checks. We use MRs consisting of an unordered set of *attributes* and their *values* and collect multiple corresponding natural language texts (references) – utterances consisting of one or several sentences. An example MR-reference pair is shown in Figure 1, Table 1 lists all the attributes in our domain.

In contrast to previous work (Mairesse et al., 2010; Wen et al., 2015a; Dušek and Jurčiček, 2016), we use different modalities of meaning representation for data collection: textual/logical and pictorial MRs. The textual/logical MRs (see Figure 1) take the form of a sequence with attribute-value pairs provided in a random order. The pictorial MRs (see Figure 2) are semi-automatically generated pictures with a combination of icons corresponding to the appropriate attributes. The icons are located on a background showing a map of a city, thus allowing to represent the meaning of attributes *area* and *near* (cf. Table 1).

In a pre-study (Novikova et al., 2016), we showed that pictorial MRs provide similar collection speed and utterance length, but are less likely to prime the crowd workers in their lexical choices. Utterances produced using pictorial MRs were considered to be more informative, natural and better phrased. However, while pictorial MRs provide more variety in the utterances, this also introduces noise. Therefore, we decided to use pictorial MRs to collect 20% of the dataset.

Our crowd workers were asked to verbalise all information from the MR; however, they were not



Figure 2: An example pictorial MR.

E2E data part	MRs	References
training set	4,862	42,061
development set	547	4,672
test set	630	4,693
full dataset	6,039	51,426

Table 2: Total number of MRs and human references in the E2E data sections.

penalised for skipping an attribute. This makes the dataset more challenging, as NLG systems need to account for noise in training data. On the other hand, the systems are helped by having multiple human references per MR at their disposal.

2.2 Data Statistics

The resulting dataset (Novikova et al., 2017b) contains over 50k references for 6k distinct MRs (cf. Table 2), which is 10 times bigger than previous sets in comparable domains (BAGEL, SF Hotels/Restaurants, RoboCup). The dataset contains more human references per MR (8.27 on average), which should make it more suitable for data-driven approaches. However, it is also more challenging as it uses a larger number of sentences in references (up to 6 compared to 1–2 in other sets) and more attributes in MRs.

For the E2E challenge, we split the data into training, development and test sets (in a roughly 82-9-9 ratio). MRs in the test set are all previously unseen, i.e. none of them overlaps with training/development sets, even if restaurant names are removed. MRs for the test set were only released to participants two weeks before the challenge submission deadline on October 31, 2017. Participants had no access to test reference texts. The whole dataset is now freely available at the E2E NLG Challenge website at:

<http://www.macs.hw.ac.uk/InteractionLab/E2E/>

System	BLEU	NIST	METEOR	ROUGE-L	CIDEr	norm. avg.
♥ TGEN baseline (Novikova et al., 2017b): seq2seq with MR classifier reranking	0.6593	8.6094	0.4483	0.6850	2.2338	0.5754
♥ SLUG (Juraska et al., 2018): seq2seq-based ensemble (LSTM/CNN encoders, LSTM decoder), heuristic slot aligner reranking, data augmentation	0.6619	8.6130	0.4454	0.6772	2.2615	0.5744
♥ TNT1 (Oraby et al., 2018): TGEN with data augmentation	0.6561	8.5105	0.4517	0.6839	2.2183	0.5729
♥ NLE (Agarwal et al., 2018): fully lexicalised character-based seq2seq with MR classification reranking	0.6534	8.5300	0.4435	0.6829	2.1539	0.5696
♥ TNT2 (Tandon et al., 2018): TGEN with data augmentation	0.6502	8.5211	0.4396	0.6853	2.1670	0.5688
♥ HARV (Gehrmann et al., 2018): fully lexicalised seq2seq with copy mechanism, coverage penalty reranking, diverse ensembling	0.6496	8.5268	0.4386	0.6872	2.0850	0.5673
♥ ZHANG (Zhang et al., 2018): fully lexicalised seq2seq over subword units, attention memory	0.6545	8.1840	0.4392	0.7083	2.1012	0.5661
♥ GONG (Gong, 2018): TGEN fine-tuned using reinforcement learning	0.6422	8.3453	0.4469	0.6645	2.2721	0.5631
♥ TRI (Schilder et al., 2018): seq2seq with stronger delexicalization (incl. <i>priceRange</i> and <i>customerRating</i>)	0.6336	8.1848	0.4322	0.6828	2.1425	0.5563
◇ SHEFF1 (Chen et al., 2018): 2-level linear classifiers deciding on next slot/token, trained using LOLS, training data filtering	0.6015	8.3075	0.4405	0.6778	2.1775	0.5537
♣ DANGNT (Nguyen and Tran, 2018): rule-based two-step approach, selecting phrases for each slot + lexicalising	0.5990	7.9277	0.4346	0.6634	2.0783	0.5395
♥ SLUG-ALT (<i>late submission</i> , Juraska et al., 2018): SLUG trained only using complex sentences from the training data	0.6035	8.3954	0.4369	0.5991	2.1019	0.5378
◇ ZHAW2 (Deriu and Cieliebak, 2018): semantically conditioned LSTM RNN language model (Wen et al., 2015b) + controlling the first generated word	0.6004	8.1394	0.4388	0.6119	1.9188	0.5314
♣ TUDA (Puzikov and Gurevych, 2018): handcrafted templates	0.5657	7.4544	0.4529	0.6614	1.8206	0.5215
◇ ZHAW1 (Deriu and Cieliebak, 2018): ZHAW2 with MR classification loss + reranking	0.5864	8.0212	0.4322	0.5998	1.8173	0.5205
♥ ADAPT (Elder et al., 2018): seq2seq with preprocessing that enriches the MR with desired target words	0.5092	7.1954	0.4025	0.5872	1.5039	0.4738
♥ CHEN (Chen, 2018): fully lexicalised seq2seq with copy mechanism and attention memory	0.5859	5.4383	0.3836	0.6714	1.5790	0.4685
♣ FORGE3 (Mille and Dasiopoulou, 2018): templates mined from training data	0.4599	7.1092	0.3858	0.5611	1.5586	0.4547
♥ SHEFF2 (Chen et al., 2018): vanilla seq2seq	0.5436	5.7462	0.3561	0.6152	1.4130	0.4462
♣ TR2 (Schilder et al., 2018): templates mined from training data	0.4202	6.7686	0.3968	0.5481	1.4389	0.4372
♣ FORGE1 (Mille and Dasiopoulou, 2018): grammar-based	0.4207	6.5139	0.3685	0.5437	1.3106	0.4231

Table 3: A list of primary systems in the E2E NLG challenge, with word-overlap metric scores.

System architectures are coded with colours and symbols: ♥ seq2seq, ◇ other data-driven, ♣ rule-based, ♣ template-based. Unless noted otherwise, all data-driven systems use partial delexicalisation (with *name* and *near* attributes replaced by placeholders during generation), template- and rule-based systems delexicalise all attributes. In addition to word-overlap metrics (see Section 4.1), we show the average of all metrics’ values normalised into the 0-1 range, and use this to sort the list. Any values higher than the baseline are marked in bold.

3 Systems in the Competition

The interest in the E2E Challenge has by far exceeded our expectations. We received a total of 62 submitted systems by 17 institutions (about 1/3 from industry). In accordance with ethical considerations for NLP shared tasks (Parra Escartín et al., 2017), we allowed researchers to withdraw or anonymise their results if their system performs in the lower 50% of submissions. Two groups from industry withdrew their submissions and one group asked to be anonymised after obtaining automatic evaluation results.

We asked each of the remaining teams to identify 1-2 primary systems, which resulted in 20 systems by 14 groups. Each primary system is described in a short technical paper (available on the challenge website) and was evaluated both by automatic metrics and human judges (see Sec-

tion 4). We compare the primary systems to a baseline based on the TGEN generator (Dušek and Jurčiček, 2016a). An overview of all primary systems is given in Table 3, including the main features of their architectures. A more detailed description and comparison of systems will be given in (Dušek et al., 2018).

4 Evaluation Results

4.1 Word-overlap Metrics

Following previous shared tasks in related fields (Bojar et al., 2017b; Chen et al., 2015), we selected a range of metrics measuring word-overlap between system output and references, including BLEU, NIST, METEOR, ROUGE-L, and CIDEr. Table 3 summarises the primary system scores. The TGEN baseline is very strong in terms of word-overlap metrics: No primary system is able

	#	TrueSkill	Rank	System		#	TrueSkill	Rank	System	
Quality	1	0.300	1–1	♥ SLUG	Naturalness	1	0.211	1–1	♥ SHEFF2	
		0.228	2–4	♠ TUDA			0.171	2–3	♥ SLUG	
		0.213	2–5	♥ GONG			0.154	2–4	♥ CHEN	
		0.184	3–5	♣ DANGNT			0.126	3–6	♥ HARV	
		0.184	3–6	♥ TGEN			0.105	4–8	♥ NLE	
		0.136	5–7	♥ SLUG-ALT (late)			0.101	4–8	♥ TGEN	
		0.117	6–8	♠ ZHAW2			2	0.091	5–8	♣ DANGNT
		0.084	7–10	♥ TNT1			0.077	5–10	♠ TUDA	
		0.065	8–10	♥ TNT2			0.060	7–11	♥ TNT2	
		0.048	8–12	♥ NLE			0.046	9–12	♥ GONG	
		0.018	10–13	♠ ZHAW1			0.027	9–12	♥ TNT1	
		0.014	10–14	♣ FORGE1			0.027	10–12	♥ ZHANG	
		-0.012	11–14	♠ SHEFF1			-0.053	13–16	♥ TR1	
		-0.012	11–14	♥ HARV			-0.073	13–17	♥ SLUG-ALT (late)	
		3	-0.078	15–16			♠ TR2	3	-0.077	13–17
-0.083	15–16	♠ FORGE3	-0.083	13–17	♠ ZHAW2					
-0.152	17–19	♥ ADAPT	-0.104	15–17	♠ ZHAW1					
4	-0.185	17–19	♥ TRI	4	-0.144	18–19	♣ FORGE1			
-0.186	17–19	♥ ZHANG	-0.164	18–19	♥ ADAPT					
5	-0.426	20–21	♥ CHEN	5	-0.243	20–21	♠ TR2			
-0.457	20–21	♥ SHEFF2	-0.255	20–21	♠ FORGE3					

Table 4: TrueSkill measurements of *quality* (left) and *naturalness* (right).

Significance cluster number, TrueSkill value, range of ranks where the system falls in 95% of cases or more, system name. Significance clusters are separated by a dotted line. Systems are colour-coded by architecture as in Table 3.

to beat it in terms of all metrics – only SLUG comes very close. Several other systems beat TGEN in one of the metrics but not in others.³ Overall, seq2seq-based systems show the best word-based metric values, followed by SHEFF1, a data-driven system based on imitation learning. Template-based and rule-based systems mostly score at the bottom of the list.

4.2 Results of Human Evaluation

However, the human evaluation study provides a different picture. Rank-based Magnitude Estimation (RankME) (Novikova et al., 2018) was used for evaluation, where crowd workers compared outputs of 5 systems for the same MR and assigned scores on a continuous scale. We evaluated output naturalness and overall quality in separate tasks; for naturalness evaluation, the source MR was not shown to workers. We collected 4,239 5-way rankings for naturalness and 2,979 for quality, comparing 9.5 systems per MR on average.

The final evaluation results were produced using the TrueSkill algorithm (Herbrich et al., 2006; Sakaguchi et al., 2014), with partial ordering into significance clusters computed using bootstrap resampling (Bojar et al., 2013, 2014; Sakaguchi et al., 2014). For both criteria, this resulted in 5

clusters of systems with significantly different performance and showed a clear winner: SHEFF2 for *naturalness* and SLUG for *quality*. The 2nd clusters are quite large for both criteria – they contain 13 and 11 systems, respectively, and both include the baseline TGEN system.

The results indicate that seq2seq systems dominate in terms of *naturalness* of their outputs, while most systems of other architectures score lower. The bottom cluster is filled with template-based systems. The results for *quality* are, however, more mixed in terms of architectures, with none of them clearly prevailing. Here, seq2seq systems with reranking based on checking output correctness score high while seq2seq systems with no such mechanism occupy the bottom two clusters.

5 Conclusion

This paper presents the first shared task on end-to-end NLG. The aim of this challenge was to assess the capabilities of recent end-to-end, fully data-driven NLG systems, which can be trained from pairs of input MRs and texts, without the need for fine-grained semantic alignments. We created a novel dataset for the challenge, which is an order-of-magnitude bigger than any previous publicly available dataset for task-oriented NLG. We received 62 system submissions by 17 participating institutions, with a wide range of architectures, from seq2seq-based models to simple templates.

³Note, however, that several secondary system submissions perform better than the primary ones (and the baseline) with respect to word-overlap metrics.

We evaluated all the entries in terms of five different automatic metrics; 20 primary submissions (as identified by the 14 remaining participants) underwent crowdsourced human evaluation of naturalness and overall quality of their outputs.

We consider the SLUG system (Juraska et al., 2018), a seq2seq-based ensemble system with a reranker, as the overall winner of the E2E NLG challenge. SLUG scores best in human evaluations of quality, it is placed in the 2nd-best cluster of systems in terms of naturalness and reaches high automatic scores. While the SHEFF2 system (Chen et al., 2018), a vanilla seq2seq setup, won in terms of naturalness, it scores poorly on overall quality – it placed in the last cluster. The TGEN baseline system turned out hard to beat: It ranked highest on average in word-overlap-based automatic metrics and placed in the 2nd cluster in both quality and naturalness.

The results in general show the seq2seq architecture as very capable, but requiring reranking to reach high-quality results. On the other hand, while rule-based approaches are not able to beat data-driven systems in terms of automatic metrics, they often perform comparably or better in human evaluations.

We are preparing a detailed analysis of the results (Dušek et al., 2018) and a release of all system outputs with user ratings on the challenge website.⁴ We plan to use this data for experiments in automatic NLG output quality estimation (Specia et al., 2010; Dušek et al., 2017), where the large amount of data obtained in this challenge allows a wider range of experiments than previously possible.

Acknowledgements

This research received funding from the EPSRC projects DILiGENT (EP/M005429/1) and MaDrIGAL (EP/N017536/1). The Titan Xp used for this research was donated by the NVIDIA Corporation.

References

Shubham Agarwal, Marc Dymetman, and Éric Gaussier. 2018. Char2char generation with reranking for the E2E NLG Challenge. In *Proceedings of INLG*.

⁴<http://www.macs.hw.ac.uk/InteractionLab/E2E>

Anja Belz and Albert Gatt. 2007. *The attribute selection for GRE challenge: Overview and evaluation results*. In *Proceedings of MT Summit*, pages 75–83, Copenhagen, Denmark.

Ondřej Bojar, Rajen Chatterjee, Christian Federmann, Yvette Graham, Barry Haddow, Shujian Huang, Matthias Huck, Philipp Koehn, Qun Liu, Varvara Logacheva, et al. 2017a. *Findings of the 2017 conference on machine translation (WMT17)*. In *Proceedings of WMT*, pages 169–214, Copenhagen, Denmark.

Ondřej Bojar, Christian Buck, Chris Callison-Burch, Christian Federmann, Barry Haddow, Philipp Koehn, Christof Monz, Matt Post, Radu Soricut, and Lucia Specia. 2013. *Findings of WMT*. In *Proceedings of WMT*, pages 1–44, Sofia, Bulgaria.

Ondřej Bojar, Christian Buck, Christian Federmann, Barry Haddow, Philipp Koehn, Johannes Leveling, Christof Monz, Pavel Pecina, Matt Post, Herve Saint-Amand, Radu Soricut, Lucia Specia, and Aleš Tamchyna. 2014. *Findings of the 2014 Workshop on Statistical Machine Translation*. In *Proceedings of WMT*, pages 12–58, Baltimore, Maryland, USA.

Ondřej Bojar, Yvette Graham, and Amir Kamran. 2017b. *Results of the WMT17 Metrics Shared Task*. In *Proceedings of WMT*, pages 489–513, Copenhagen, Denmark.

David L. Chen and Raymond J. Mooney. 2008. *Learning to sportscast: A test of grounded language acquisition*. In *Proceedings of ICML*, pages 128–135, Helsinki, Finland.

Mingje Chen, Gerasimos Lampouras, and Andreas Vlachos. 2018. *Sheffield at E2E: structured prediction approaches to end-to-end language generation*. In *E2E NLG Challenge System Descriptions*.

Shuang Chen. 2018. *A General Model for Neural Text Generation from Structured Data*. In *E2E NLG Challenge System Descriptions*.

Xinlei Chen, Hao Fang, Tsung-Yi Lin, Ramakrishna Vedantam, Saurabh Gupta, Piotr Dollar, and C. Lawrence Zitnick. 2015. *Microsoft COCO Captions: Data Collection and Evaluation Server*. *CoRR*, abs/1504.00325.

Jan Deriu and Mark Cieliebak. 2018. *End-to-End Trainable System for Enhancing Diversity in Natural Language Generation*. In *E2E NLG Challenge System Descriptions*.

Ondřej Dušek, Jekaterina Novikova, and Verena Rieser. 2018. The E2E NLG Challenge. In *(in prep.)*.

Ondřej Dušek and Filip Jurčiček. 2015. *Training a natural language generator from unaligned data*. In *Proceedings of ACL-IJCNLP*, pages 451–461, Beijing, China.

- Ondřej Dušek and Filip Jurčiček. 2016. [A Context-aware Natural Language Generator for Dialogue Systems](#). In *Proceedings of SIGDIAL*, pages 185–190, Los Angeles, CA, USA.
- Ondřej Dušek and Filip Jurčiček. 2016a. [Sequence-to-sequence generation for spoken dialogue via deep syntax trees and strings](#). In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics*, pages 45–51, Berlin, Germany. arXiv:1606.05491.
- Ondřej Dušek, Jekaterina Novikova, and Verena Rieser. 2017. [Referenceless Quality Estimation for Natural Language Generation](#). In *Proceedings of the 1st Workshop on Learning to Generate Natural Language (LGNL)*, Sydney, Australia. ArXiv:1708.01759.
- Henry Elder, Sebastian Gehrmann, Alexander O’Connor, and Qun Liu. 2018. [E2E NLG Challenge Submission: Towards Controllable Generation of Diverse Natural Language](#). In *Proceedings of INLG*.
- Claire Gardent, Anastasia Shimorina, Shashi Narayan, and Laura Perez-Beltrachini. 2017. [The WebNLG Challenge: Generating text from RDF data](#). In *Proceedings of INLG*, pages 124–133, Santiago de Compostela, Spain.
- Albert Gatt and Emiel Kraemer. 2018. [Survey of the State of the Art in Natural Language Generation: Core tasks, applications and evaluation](#). *Journal of Artificial Intelligence Research (JAIR)*, 61:65–170.
- Sebastian Gehrmann, Falcon Z. Dai, Henry Elder, and Alexander M. Rush. 2018. [End-to-End Content and Plan Selection for Natural Language Generation](#). In *E2E NLG Challenge System Descriptions*.
- Heng Gong. 2018. [Technical Report for E2E NLG Challenge](#). In *E2E NLG Challenge System Descriptions*.
- Ralf Herbrich, Tom Minka, and Thore Graepel. 2006. [TrueSkill™: a Bayesian skill rating system](#). In *Proceedings of NIPS*, pages 569–576, Vancouver, Canada.
- Juraj Juraska, Panagiotis Karagiannis, Kevin K. Bowden, and Marilyn A. Walker. 2018. [A Deep Ensemble Model with Slot Alignment for Sequence-to-Sequence Natural Language Generation](#). In *Proceedings of NAACL-HLT*, New Orleans, LA, USA.
- Gerasimos Lampouras and Andreas Vlachos. 2016. [Imitation learning for language generation from unaligned data](#). In *Proceedings of COLING*, pages 1101–1112, Osaka, Japan.
- François Mairesse, Milica Gašić, Filip Jurčiček, Simon Keizer, Blaise Thomson, Kai Yu, and Steve Young. 2010. [Phrase-based statistical language generation using graphical models and active learning](#). In *Proceedings of ACL*, pages 1552–1561, Uppsala, Sweden.
- Hongyuan Mei, Mohit Bansal, and Matthew R. Walter. 2016. [What to talk about and how? Selective generation using LSTMs with coarse-to-fine alignment](#). In *Proceedings of NAACL-HLT*, San Diego, CA, USA.
- Simon Mille and Stamatia Dasiopoulou. 2018. [FORGe at E2E 2017](#). In *E2E NLG Challenge System Descriptions*.
- Dang Tuan Nguyen and Trung Tran. 2018. [Structure-based Generation System for E2E NLG Challenge](#). In *E2E NLG Challenge System Descriptions*.
- Jekaterina Novikova, Ondřej Dušek, Amanda Cercas Curry, and Verena Rieser. 2017a. [Why we need new evaluation metrics for NLG](#). In *Proceedings of EMNLP*, pages 2231–2242.
- Jekaterina Novikova, Ondřej Dušek, and Verena Rieser. 2017b. [The E2E Dataset: New Challenges for End-to-End Generation](#). In *Proceedings of SIGDIAL*, pages 201–206, Saarbrücken, Germany.
- Jekaterina Novikova, Ondřej Dušek, and Verena Rieser. 2018. [RankME: Reliable Human Ratings for Natural Language Generation](#). In *Proceedings of NAACL-HLT*, pages 72–78, New Orleans, LA, USA.
- Jekaterina Novikova, Oliver Lemon, and Verena Rieser. 2016. [Crowd-sourcing NLG data: Pictures elicit better data](#). In *Proceedings of INLG*, pages 265–273, Edinburgh, UK. arXiv:1608.00339.
- Shereen Oraby, Lena Reed, Shubhangi Tandon, Sharath T.S., Stephanie Lukin, and Marilyn Walker. 2018. [TNT-NLG, System 1: Using a statistical NLG to massively augment crowd-sourced data for neural generation](#). In *E2E NLG Challenge System Descriptions*.
- Carla Parra Escartín, Wessel Reijers, Teresa Lynn, Joss Moorkens, Andy Way, and Chao-Hong Liu. 2017. [Ethical considerations in NLP shared tasks](#). In *Proceedings of the First ACL Workshop on Ethics in Natural Language Processing*, pages 66–73.
- Yevgeniy Puzikov and Iryna Gurevych. 2018. [E2E NLG Challenge: Neural Models vs. Templates](#). In *Proceedings of INLG*.
- E. Reiter and R. Dale. 2000. *Building Natural Language Generation Systems*, studies in natural language processing edition. Cambridge University Press.
- Keisuke Sakaguchi, Matt Post, and Benjamin Van Durme. 2014. [Efficient elicitation of annotations for human evaluation of machine translation](#). In *Proceedings of WMT*, pages 1–11, Baltimore, MD, USA.
- Frank Schilder, Charese Smiley, Elnaz Davoodi, and Dezhao Song. 2018. [The E2E NLG Challenge: A tale of two systems](#). In *Proceedings of INLG*.

- Shikhar Sharma, Jing He, Kaheer Suleman, Hannes Schulz, and Philip Bachman. 2016. [Natural language generation in dialogue using lexicalized and delexicalized data](#). *CoRR*, abs/1606.03632.
- Lucia Specia, Dhvaj Raj, and Marco Turchi. 2010. [Machine translation evaluation versus quality estimation](#). *Machine translation*, 24(1):39–50.
- Shubhangi Tandon, Sharath T.S., Shereen Oraby, Lena Reed, Stephanie Lukin, and Marilyn Walker. 2018. [TNT-NLG, System 2: Data repetition and meaning representation manipulation to improve neural generation](#). In *E2E NLG Challenge System Descriptions*.
- Tsung-Hsien Wen, Milica Gasić, Dongho Kim, Nikola Mrkšić, Pei-Hao Su, David Vandyke, and Steve Young. 2015a. [Stochastic language generation in dialogue using recurrent neural networks with convolutional sentence reranking](#). In *Proceedings of SIG-DIAL*, pages 275–284, Prague, Czech Republic.
- Tsung-Hsien Wen, Milica Gasić, Nikola Mrkšić, Lina Maria Rojas-Barahona, Pei-hao Su, David Vandyke, and Steve J. Young. 2016. [Multi-domain neural network language generation for spoken dialogue systems](#). In *Proceedings of NAACL-HLT*, pages 120–129, San Diego, CA, USA.
- Tsung-Hsien Wen, Milica Gasić, Nikola Mrkšić, Pei-Hao Su, David Vandyke, and Steve Young. 2015b. [Semantically conditioned LSTM-based natural language generation for spoken dialogue systems](#). In *Proceedings of EMNLP*, pages 1711–1721, Lisbon, Portugal.
- Sam Wiseman, Stuart M. Shieber, and Alexander M. Rush. 2017. [Challenges in data-to-document generation](#). In *Proceedings of EMNLP*, pages 2253–2263, Copenhagen, Denmark.
- Biao Zhang, Jing Yang, Qian Lin, and Jinsong Su. 2018. [Attention Regularized Sequence-to-Sequence Learning for E2E NLG Challenge](#). In *E2E NLG Challenge System Descriptions*.