

# Maximum Number of Steps of Topswops on 18 and 19 Cards

Kento Kimura, Atsuki Takahashi, Tetsuya Araki, Kazuyuki Amano\*

March 16, 2021

## Abstract

Let  $f(n)$  be the maximum number of steps of *Topswops* on  $n$  cards. In this note, we report our computational experiments to determine the values of  $f(18)$  and  $f(19)$ . By applying an algorithm developed by Knuth in a parallel fashion, we conclude that  $f(18) = 191$  and  $f(19) = 221$ .

## 1 Introduction

Consider a deck of  $n$  cards numbered 1 to  $n$  arranged in random order, which can be viewed as a permutation on  $\{1, 2, \dots, n\}$ . Continue the following operation until the top card is 1. If the top card of the deck is  $k$ , then turn over a block of  $k$  cards at the top of the deck. This card game is called *Topswops*, which was originally invented by J.H. Conway in 1973. See e.g., the introduction of [4] for a short history of the game.

The problem is to find an initial deck that requires a maximum number of steps until termination, for a given number of cards. For a positive integer  $n$ , let  $f(n)$  be the maximum number of steps until termination for *Topswops* on  $n$  cards. We call an initial deck that needs  $f(n)$  steps *largest*. For example, the deck  $(3, 1, 4, 5, 2)$  is largest for  $n = 5$ . The game goes as

$$\begin{aligned} (3, 1, 4, 5, 2) &\rightarrow (4, 1, 3, 5, 2) \rightarrow (5, 3, 1, 4, 2) \rightarrow (2, 4, 1, 3, 5) \\ &\rightarrow (4, 2, 1, 3, 5) \rightarrow (3, 1, 2, 4, 5) \rightarrow (2, 1, 3, 4, 5) \rightarrow (1, 2, 3, 4, 5), \end{aligned} \quad (1)$$

and terminates after  $f(5) = 7$  steps.

The best known upper bound on  $f(n)$  is  $F(n+1) - 1 = O(1.618^n)$ , where  $F(k)$  is the  $k$ -th Fibonacci number [2, Problems 107–109] and the best known lower bound is  $\Omega(n^2)$  [4]. The gap is exponential. The exact values of  $f(n)$  for  $n \leq 17$  have been obtained by an exhaustive search with some pruning techniques. The sequence is  $(0, 1, 2, 4, 7, 10, 16, 22, 30, 38, 51, 65, 80, 101, 113, 139, 159)$  for  $n = 1, 2, \dots, 17$ . See the sequence A000375 of OEIS [5].

In this note, we describe our effort for extending this list for  $n = 18$  and 19. Namely, by applying an algorithm developed by Knuth [3] in a parallel fashion, we conclude that  $f(18) = 191$  and  $f(19) = 221$ . We also find that the number of initial decks that attain the maximum for

---

\*All authors are at Department of Computer Science, Gunma University

$n = 18$  is one and that for  $n = 19$  is four, respectively. Note that the values for  $n \leq 17$  are listed as the sequence A123398 at OEIS [5].

The rest of this note is as follows. In Section 2, we give a brief explanation of Knuth’s algorithm [2]. Then, in Section 3, we describe our computational experiments for determining  $f(18)$  and  $f(19)$ . The code used in our experiments can be viewed on GitLab at <https://gitlab.com/kkimura/tswops>.

## 2 Knuth’s algorithm

In this section, we explain an algorithm for finding a largest deck for Topswops used in our experiment, which was developed by Knuth [2, Solution of Problem 107] (see also [3] for the code itself). Three algorithms were described there and we use the most efficient one, which is referred to as a “better” algorithm.

For a natural number  $n$ , let  $[n]$  denote the set  $\{1, 2, \dots, n\}$ . For an initial deck  $A$ , let  $S(A)$  be a list  $(d_1, d_2, \dots, d_k)$  ( $k \leq n$ ) where  $d_i$  is the  $i$ -th card that appeared at the top of the deck in the game starting from  $A$ . For example,  $S((3, 1, 4, 5, 2)) = (3, 4, 5, 2, 1)$  (see Eq. (1)) and  $S((3, 5, 4, 1, 2)) = (3, 4, 1)$ . Notice that the length of  $S(A)$  depends on  $A$ , but the last element of  $S(A)$  is always 1. An important property is that if  $A$  is largest, then the length of  $S(A)$  must be  $n$ . This can be verified by seeing that if  $S(A) = (d_1, \dots, d_{k-1}, 1)$  for some  $k < n$ , then we can always create another deck  $A'$  such that the first  $k$  elements of  $S(A')$  is  $(d_1, \dots, d_{k-1}, d')$  for  $d' \in \{2, \dots, n\} \setminus \{d_1, \dots, d_{k-1}\}$  and that the game for  $A'$  is strictly longer than the one for  $A$ .

Let  $P$  be the set of all lists  $p = (p_1, p_2, \dots, p_n)$  such that  $p$  is a permutation on  $[n]$  and  $p_n = 1$ . Given a list  $p \in P$ , we can get an initial deck  $S^{-1}(p)$  by the following algorithm. In Algorithm 1, the minus value  $-i$  in  $A$  means that the  $i$ -th card in a deck is not specified yet.

---

### Algorithm 1 Generate an Initial Deck

---

```

1: procedure GENINITDECK( $p$ )
2:   Let  $A$  be an array with  $(-1, -2, \dots, -n)$ .
3:   for  $i = 1, 2, \dots, n$  do
4:      $a_{-i} := p_i$ 
5:      $A_1 := p_i$ 
6:     while  $A_1 > 1$  do
7:       Turn over a block of  $A_1$  cards of  $A$ .
8:   return  $(a_i)_{i \in [n]}$ 

```

---

The above arguments suggest that we can determine  $f(n)$  by examining all  $(n - 1)!$  lists in  $P$  together with Algorithm 1. Essentially, Knuth’s algorithm enumerates these lists as well as corresponding decks in a depth-first fashion. Moreover, the algorithm applies two pruning criteria to reduce the size of the search tree.

The first pruning is based on the fact that a largest deck must be a *derangement*, i.e., the  $k$ -th card from the top is not  $k$  for every  $k \in [n]$ . In order to explain the second pruning, we need some definitions. Let  $A$  be an initial deck and let  $A_c$  be the deck obtained from  $A$  by executing  $c$  steps of the game. Let  $T(A_c)$  denote the largest integer  $k$  such that the cards numbered  $1, 2, \dots, k$

are located at positions at  $1, 2, \dots, k$  (in an arbitrary order) in the deck  $A$ . It is obvious that if  $f(T(A)) + c < f(n)$ , then  $A$  is not largest. Although  $f(n)$  is not known beforehand, we can use any lower bound  $\ell(n)$  on  $f(n)$  in the right hand side of inequalities for pruning.

Note that the depth of the search tree without pruning is  $(n - 1)$  and each node at depth  $k$  has  $n - 1 - k$  children.

### 3 Experiments and Results

Since the search tree of Knuth's "better" algorithm is well-balanced, it is easy to be parallelized. First, we generate the search tree for the first few levels, which corresponds to the first few elements of the list  $p$  explained in the last section. Then, distribute the leaves of the tree to many threads and resume the generation in parallel by letting a given leaf as a root of a subtree.

For  $n = 18$ , we truncate the tree at level two and divide it into 240 subtrees. For  $n = 19$ , we truncate the tree at level three and divide it into 3,952 subtrees. Each of these numbers is slightly smaller than the one in the original search tree, i.e.,  $272 (= 17 \times 16)$  or  $4,080 (= 18 \times 17 \times 16)$ , because of the pruning.

In our experiments, we use up to 172 threads in parallel spreading out over nine standard PCs. The computation takes about 7 hours for  $n = 18$  (using 132 threads), and about 6 days for  $n = 19$  (using 172 threads). This means that, if we run the code on a single thread, then the computation would take approximately  $10^3$  days for  $n = 19$ . The total numbers of traversed nodes are 43,235,268,208,065 for  $n = 18$  and 933,351,108,741,643 for  $n = 19$ , respectively. The ratios to the number of nodes in the search tree without pruning, i.e.,  $\sum_{j=0}^{n-1} \prod_{i=1}^j (n - i)$ , are 4.47% and 5.36%, respectively. The breakdown of the number of traversed nodes for  $n = 19$  with respect to the levels of the tree is shown in Table 1.

By examining the result, we conclude that  $f(18) = 191$  and  $f(19) = 221$ . The largest initial deck for  $n = 18$  is unique. It is

(6 14 9 2 15 8 1 3 4 12 18 5 10 13 16 17 11 7),

which terminates at the sorted position (1 2 3 ... 18). There are four largest initial decks for  $n = 19$ . These are

(9 4 19 17 10 1 11 15 12 8 5 2 18 13 16 7 3 14 6),  
 (12 15 11 1 10 17 19 2 5 8 9 4 18 13 16 7 3 14 6),  
 (12 1 18 11 3 14 2 6 8 16 5 4 15 10 13 17 19 7 9),  
 (12 1 18 11 2 3 14 6 8 16 5 4 15 10 13 17 19 7 9).

Interestingly, all these decks terminate at a same non-sorted position (1 10 9 8 7 6 5 4 3 2 11 12 13 14 15 16 17 18 19). The largest initial deck that terminates at the sorted position is known to take 209 steps (see A000376 of OEIS [5]), which is twelve less than the value of  $f(19)$ .

### Acknowledgements

This work was partially supported by JSPS Kakenhi Grant Numbers 18K11152 and 18H04090.

Table 1: The number of traversed nodes for  $n = 19$ .

Level	# of traversed nodes	Level	# of traversed nodes
0	1	10	46335514956
1	17	11	304773283939
2	272	12	1716889839183
3	3952	13	8059154346527
4	52861	14	30428256670076
5	653126	15	89242470628183
6	7419100	16	200111553921243
7	77075852	17	326581145735086
8	726678384	18	276853558861087
9	6158057798	-----	
10	46335514956	Total	933351108741643

## References

- [1] D. Berman, M. S. Klamkin and D. E. Knuth, Problem 76-17. A reverse card shuffle, SIAM Review 19, pp. 739–741 (1977)
- [2] D.E. Knuth, The Art of Computer Programming Volume 4 Fascicle 2, Addison-Wesley Prof., pp. 119 (2005)
- [3] D.E. Knuth, “topswops-fwd.w” (the source code of a “better” algorithm), <https://www-cs-faculty.stanford.edu/~knuth/programs/topswops-fwd.w>, (accessed Mar. 3, 2021)
- [4] L. Morales, H. Sudborough, A quadratic lower bound for Topswops, Theoretical Computer Science, Vol. 411, pp. 3965–3970 (2010)
- [5] OEIS Foundation Inc., The On-Line Encyclopedia of Integer Sequences, <http://oeis.org> (2021)