



ANSI/NEMA MG 1-2011
Revision of ANSI/NEMA MG 1-2010

American National Standard

Motors and Generators

Secretariat:

National Electrical Manufacturers Association

Approved September 27, 2011
ANSI Approval Date July 7, 2012
Printed December 9, 2011

American National Standards Institute, Inc.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The National Electrical Manufacturers Association (NEMA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

< This page is intentionally left blank. >

Changes made for MG 1-2009, Revision 1-2010 are marked by an orange line to the left of the changed material

Note: Where text has been revised in more than one version, only the most recent is color-coded

Example of change made for MG 1-2009, Revision 1-2010

Section I, Part 7

7.4.2	Replaced “inches” with “mils”
7.6.1	Revised text
Figure 7-1	Renamed figure
7.8.1	Revised text
Figure 7-6	Replaced figure
Table 7-1	Revised table
7.8.2	Deleted section
7.8.3	Deleted section
7.8.4	Deleted section
7.8.5	Revised reference to table
7.8.6	Revised reference to table
7.9.1	Revised reference to table
7.9.2	Revised text and reference to table
7.9.3	Deleted section
Table 7-2	Deleted table
Table 7-3	Deleted table
Table 7-4	Added table to replace Tables 7-2 and 7-3

Section II, Part 14

14.48	Added section
-------	---------------

Changes made for MG 1-2009 are marked by a red line to the left of the changed material

Note: Where text has been revised in more than one version, only the most recent is color-coded

Example of change made for MG 1-2009

Section I, Part 1

- 1.1 Added: Reference to IEC 60034-30-2008
- 1.16 Deleted section
- 1.41.3 Added: Premium Efficiency Motor

Section I, Part 2

- 2.2 Added: "To prevent confusion with the numerals 1 and 0, the letters "I" and "O" shall not be used."
Updated footnote references
Added and revised markings
- 2.60.1.2 Added: Reference to 2.67 for auxiliary devices
- 2.67 Revised Figure 2-48B for clarity
Added: Auxiliary Devices (entire section)

Section I, Part 4

- Table 4-2 Dimension revised in column 6

Section II, Part 10

- Table 10-5 Adjusted table

Section II, Part 12

- 12.41 In table, corrected synchronous speed of the 50 Hz machine
- 12.60.3 Added: Additional paragraphs, equation, and table
- Table 12-14 Replaced Table 12-14
- 12.62 Revised 12.62a
For 12.62b and 12.62d, revised minimum insulation resistance
Added: Note
- 12.63 Note 2: Updated reference to 20.8

Section II, Part 13

- 13.2 Revised frame size

Section II, Part 18:

- 18.131 Figure 18-16: Dimension revised to 5.875

Section III, Part 20:

- 20.18.1 Revised 20.18.1a
For 20.18.1b and 20.18.1d, revised minimum insulation resistance

20.18.2 Revised 20.18.2a
 For 20.18.2b and 20.18.2d, revised minimum insulation resistance
 Added: Note

Section IV, Part 30:

Table 30-1 Revised footnote G.1 reference to 12.53

Changes made for MG 1-2006 Revision 1, published Nov. 20, 2007 (includes MG 1-2006 Errata) are marked by a blue line to the left of the changed material

Note: Where text has been revised in more than one version, only the most recent is color-coded

Example of change made for MG 1-2006 Revision 1

Contents

Entire Table of Contents was revised due to added sections and repagination

Section I, Part 1

- 1.16 NEMA PREMIUM[®] EFFICIENCY ELECTRIC MOTOR
Changed [™] to [®]
Deleted general paragraph, added:
- 1.16.1 60 Hz
- 1.16.2 50 Hz

Section I, Part 2

- 2.2 TERMINAL MARKINGS Footnotes
- 2.20.2 Induction Machines
- 2.24 DIRECTION OF ROTATION
- 2.60.1.1 Terminal Markings Using “T”
- 2.60.1.2 Terminal Markings in Accordance with IEC 60034-8 Using U, V, W
- FIGURE 2-48B Added figure
- 2.61.6 Sixth
Revised text

Section I, Part 3

- 3.1.8 Accessories and Components
Inserted sentence

Section I, Part 4

- 4.9.4 Parallelism of Keyseats to Shaft Centerline
- 4.9.5 Lateral Displacement of Keyseats
- Figure 4-7 Corrected specifications
- 4.9.8 Shaft Extension Key(s)
- Table 4-7 Corrected specifications

Section II, Part 10 Ratings—AC Motors

- 10.38 NAMEPLATE TEMPERATURE RATINGS FOR ALTERNATING-CURRENT SMALL AND UNIVERSAL MOTORS
Corrected reference 12.42.3

- 10.40.1 Medium Single-Phase and Polyphase Squirrel-Cage Motors
Corrected references in text and footnote 2
- 10.42.2 Polyphase Wound-Rotor Motors
Corrected references in text

Section II, Part 10 Ratings—DC Motors

- 10.66.2 Small Motors Except Those Rated 1/20 Horsepower and Less
Corrected footnote references

Section II, Part 12 Ratings Tests and Performance —AC Motors

- 12.42.4 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C
(Added section)
- 12.43.2 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C
(Added section)
- 12.60 EFFICIENCY LEVEL OF PREMIUM EFFICIENCY ELECTRIC MOTORS
(Added ® throughout)
- Tables 12-12 through 12-14 (Added ®)
- 12-13 FULL-LOAD EFFICIENCIES FOR 60 HZ NEMA PREMIUM® EFFICIENCY ELECTRIC MOTORS (Added ®), edited table title
- 12.62 MACHINE WITH ENCAPSULATED OR SEALED WINDINGS—CONFORMANCE TESTS
(Clarified text in b and d)

Section II, Part 12 Ratings Tests and Performance —DC Motors

- 12.67.5 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C
Added section

Section II, Part 15

- 15.41.2 Temperature Rise for Ambients Higher than 40°C
Added section

Section III, Part 20

- 20.8.1 Machines with a 1.0 Service Factor at Rated Load
Corrected reference in footnote
- 20.8.2 Machines with a 1.15 Service Factor at Service Factor Load
Corrected reference in footnote
- 20.18.1 Test for Stator Which Can Be Submerged
Clarified text in b and d
- 20.18.2 Test for Stator Which Can Be Submerged
Clarified text in b and d

Section III, Part 20

- 21.10.5 Temperature Rise for Air-Cooled Motors for Ambients Lower than 40° C, but Not Below 0° C
Deleted lower ambients in a and b
- 21.28.3 Unusual Service Conditions
Corrected references in subclause b.
- 21.37 COMPRESSOR FACTORS
Corrected reference
- 21.38 SURGE CAPABILITIES OF AC WINDINGS WITH FORM-WOUND COILS
Corrected reference

Section III, Part 23

- 23.9.3 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C
Added section

Section III, Part 24

- 24.40.3 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C
Added section

Section IV, Part 31

- 31.4.1.6 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C
Added section

Section IV, Part 32

- Table 32-3 corrected reference
- 32.6.2 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C
Added section
- 32.26 GENERATOR TERMINAL HOUSING
Added "housing"

Section IV, Part 33

- 33.3.2.5 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C
Added section

Changes made for MG 1-2003 Revision 2, published as MG 1-2006, are marked by a purple line to the left of the changed material

Note: Where text has been revised in more than one version, only the most recent is color-coded

Example of change made for MG 1-2003 Revision 2, published as MG 1-2006

Section I, Part 1

- 1.1 Referenced Standards updated to reflect current editions
- 1.70 NAMEPLATE MARKING
Entire section added

Section I, Part 3

- 3.1.8 Accessories and Components
Correction
- 3.1.11 Tests of an Assembled Group of Machines and Apparatus
Correction

Section I, Part 4

- 4.4.1 Dimensions for Alternating-Current Foot-Mounted Machines with Single Straight-Shaft
Extension
Notes correction
- 4.4.2 Notes correction
- 4.4.3 Notes correction
- 4.5.1 Notes correction
- 4.5.2 Notes correction
- 4.5.3 Notes
- 4.9.3 Bottom of Keyseat to Shaft Surface
- Figure 4-7 Corrected dimension
- 4.9.8 Shaft Extension Key(s)
correction

Section I, Part 9

- 9.1 SCOPE
changed "electrical motors" to "machines"
- 9.4 METHODS OF MEASUREMENT
updated references to ANSI standards
- 9.4.2 "The" (added; "Either" deleted) method specified in ANSI S12.56 may be used.
- 9.6.2 Corrected reference to 9.6.2b
- Table 9-4 Updated ANSI standard references; added third column

Section II, Part 10

- 10.39 corrected section reference
- 10.39.6 deleted

- 10.40.1 Medium Single-Phase and Polyphase Squirrel-Cage Motors
corrected section reference
- 10.66 NAMEPLATE MARKING
correction
- 10.66.3 Medium Motors
correction

Section II, Part 12

- 12.3 HIGH-POTENTIAL TEST VOLTAGES FOR UNIVERSAL, INDUCTION, AND DIRECT-CURRENT MOTORS
Corrections to Effective Test Voltage
Corrections to Note 3— 80 percent
- 12.35 LOCKED-ROTOR CURRENT OF 3-PHASE SMALL AND MEDIUM SQUIRREL-CAGE INDUCTION MOTORS
deleted reference “60-hertz” and “rated at 230 volts”
- 12.40.1 Design A and B Motors
The pull-up torque of Design A and B
Added: 60- and 50-hertz
- 12.40.2 Design C Motors
The pull-up torque of Design C
Added: 60- and 50-hertz, single speed, polyphase squirrel-cage medium motors
- 12.54.1 Normal Starting Conditions
- 12.54.3 Considerations for Additional Starts
- Table 12-7 SQUIRREL-CAGE INDUCTION MOTORS
Revised specifications

Section II, Part 14

- 14.43 ASEISMATIC CAPABILITY
- Table 14-1 MEDIUM MOTORS—POLYPHASE INDUCTION
Correction to conventional specifications

Section II, Part 15

- 15.12 NAMEPLATE MARKING

Section II Part 18

Added and corrected headers throughout (editorial)

- DEFINITE PURPOSE MACHINES
- MOTORS FOR HERMETIC REFRIGERATION COMPRESSORS
- SMALL MOTORS FOR AIR CONDITIONING CONDENSERS AND EVAPORATOR FANS
- SMALL MOTORS FOR GASOLINE DISPENSING PUMPS
- SMALL MOTORS FOR HOME LAUNDRY EQUIPMENT
- MEDIUM AC POLYPHASE ELEVATOR MOTORS
- MEDIUM AC CRANE MOTORS

- MEDIUM SHELL-TYPE MOTORS FOR WOODWORKING AND MACHINE-
TOOL APPLICATIONS

- 18.9 VARIATIONS
updated reference to 12.44
- 18.27 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.41 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.52 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.74 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.101 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.111 NAMEPLATE MARKING
- 18.116 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.128 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.142 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.152 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.153 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.165 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.166 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.177 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.178 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.210 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.211 NAMEPLATE MARKING
- 18.216 NAMEPLATE MARKING (Revised reference)
- 18.225 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44
- 18.230 DIMENSIONS AND TOLERANCES FOR ALTERNATING-CURRENT OPEN AND
TOTALLY ENCLOSED WOUND-ROTOR CRANE MOTORS HAVING ANTIFRICTION
BEARINGS
Deleted note
- 18.247 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY
updated reference to 12.44

- 18.264 NAMEPLATE MARKING
- 18.269.1 AC Torque Motors
- 18.269.2 DC Torque Motors

Section III Part 20

- 20.5 VOLTAGE RATINGS (complete replacement of existing text)
- 20.7.3.1 General
- 20.8.5 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C,
but Not Below 0 ° C
Added section
- 20.10.3 Motor Torques When Customer Specifies A Custom Load Curve
Added
- 20.10.4 Motor with 4.5 pu and Lower Locked-Rotor Current
Added
- 20.11 LOAD WK2 FOR POLYPHASE SQUIRREL-CAGE INDUCTION MOTORS
- 20.24.2 Voltage Unbalance Defined
Corrected specification in example
- 20.25 For some examples of additional information that may be included on the nameplate see
1.70.2.
- 20.25.5 Deleted
- 20.27 EMBEDDED TEMPERATURE DETECTORS
Revised text and dimensions in table
- 20.31.3 Units for Capability Requirements
- 20.35.8 Test Voltage Values

Section III Part 21

- 21.5 VOLTAGE RATINGS
Revised specification
- 21.5.1 Voltage Ratings
Added
- 21.5.2 Preferred motor output/voltage rating
Added
- 21.8.3.1 General
- 21.10.5 Temperature Rise for Air-Cooled Motors for Ambients Lower than 40° C, but not Below 0°
C
Added section
- 21.11 deleted text
- 21.11.1 General
Added
- 21.11.2 Motor Torques When Customer Supplies Load Curve
- 21.25 For some examples of additional information that may be included on the nameplate see
1.70.2.
Added

Section III Part 23

23.13 EFFICIENCY
23.24 For some examples of additional information that may be included on the nameplate see
1.70.2.
Added

Section III Part 24

24.61 NAMEPLATE MARKING

Section IV Part 30

30.1.3 Power Factor Correction
Figure 30-2 THE EFFECT OF REDUCED COOLING ON THE TORQUE CAPABILITY AT REDUCED
SPEEDS OF 60 HZ NEMA DESIGN A AND B MOTORS
30.2.2.2.4 Motor Torque During Operation Above Base Speed
30.2.2.8 Voltage Stress

Section IV Part 31

31.5.1 Variable Torque Applications

Section IV Part 30

32.24 NAMEPLATE MARKING
Revised additional information

Section IV Part 30

33.3.2.2 Embedded Temperature Detectors

Index

Revised references throughout

Changes made for MG 1-2003, Revision 1-2004 are marked by a green line to the left of the changed material

Note: Where text has been revised in more than one version, only the most recent is color-coded

Example of change made for MG 1-2003 Revision 1-2004

Contents

pages vii, viii, xii, xv, xxvii

Section I, Part 5

5.1	Scope
5.3.4	Table 5-1
5.4.1	Indication of Degree of Protection
5.6	GENERAL REQUIREMENTS FOR TESTS
5.7	TESTS FOR FIRST CHARACTERISTIC NUMERAL
Table 5-3:	TEST AND ACCEPTANCE CONDITIONS FOR FIRST CHARACTERISTIC NUMERAL
5.8.1	Test Conditions
5.8.2.1	Allowable Water Leakage
5.8.2.2	Post Water Electrical Test
Figure 5-1:	STANDARD TEST FINGER NOTES—
Figure 5-2	Added: (Reproduced with permission of the IEC, which retains the copyright.)
Figure 5-3	Added: (Reproduced with permission of the IEC, which retains the copyright.)
Figure 5-4	Added: (Reproduced with permission of the IEC, which retains the copyright.)
Figure 5-5	Added: (Reproduced with permission of the IEC, which retains the copyright.)
Figure 5-6	Added: (Reproduced with permission of the IEC, which retains the copyright.)

Section II, Part 12

12.51.1	General-Purpose Alternating-Current Motors of the Open Type
Table 12-4	Note: *In the case of polyphase squirrel-cage motors, these service factors apply only to Design A, B, and C motors.
12.51.2	Other Motors
12.58.2	Efficiency of Polyphase Squirrel-Cage Medium Motors with Continuous Ratings

Section II DC SMALL AND MEDIUM MOTORS

Added Header (editorial) to odd pages

Section II, Part 14

14.3	UNUSUAL SERVICE CONDITIONS
	b. Operation where: (revised text)
	1. There is excessive departure from rated voltage or frequency, or both (see 12.44 for alternating current motors and 12.68 for direct-current motors)
	3. The alternating-current supply voltage is unbalanced by more than 1 percent (see 12.45 and 14.36)

14.42	APPLICATION OF V-BELT SHEAVES TO ALTERNATING CURRENT MOTORS HAVING ANTIFRICTION BEARINGS
14.42.1	Dimensions
14.42.1.1	Selected Motor Ratings
14.42.1.2	Other Motor Ratings
14.42.2	Radial Overhung Load Limitations
Table 14-1	Note: The width of the sheave shall be not greater than that required to transmit the indicated horsepower but in no case shall it be wider than $2(N-W) - 0.25$.
Table 14-1A	Added 2004

Section III, Part 20

20.17.2	Test Voltage—Primary Windings Footnote
---------	--

Section III, Part 21

21.35.1	Undamped Natural Frequency
---------	----------------------------

Section IV, Part 30

30.0	SCOPE
30.2.2.2.2	Torque Derating Based on Reduction in Cooling
30.2.2.2.4	Motor Torque During Operation Above Base Speed
Figure 30-4	Notes
Figure 30-4	Note: a. Standard NEMA Design A and B motors in frames per Part 13.

Index

Revised references on pages 3, 4, 5

Changes made for MG 1-2011 are marked by a pink line to the left of the changed material

Note: Where text has been revised in more than one version, only the most recent is color-coded

Example of change made for MG 1-2011

Part I, Section I

- 1.41.2 Addition of or 20.21 B
- 1.41.3 Addition of or 20.21 C

Part 12, Section II

- 12.59 Addition of RANDOM WOUND
- Table 12-11 Addition of (RANDOM WOUND) to open and enclosed motor table title
- Table 12-12 Removed open and enclosed motor table efficiency values for 6 pole 300-500HP motors and added 8 pole efficiency values
- Table 12-13 Removed table efficiency values for 6 pole 400, 450 and 500 HP motors and added 8 pole efficiency values
- Table 12-14 Removed efficiency values for 6 pole 400, 450 and 500 HP motors

Part 20, Section III

- 20.21 Revised
- 20.21A Added efficiency of polyphase squirrel cage large motors with continuous ratings
- 20.21B Added efficiency levels of energy efficient polyphase squirrel-cage random wound large induction Motors
- Table 20-A Addition of full load efficiency table
- 20.21C Addition of efficiency level of premium efficiency large electric motors
- 20.21.C.1 Addition of 60Hz motors rated 600 volts or less
- Table 20-B Addition of full load premium efficiency table
- 20.21.C.2 Addition of 60Hz motors rated 5000 volts or less
- Table 20-C Addition of full load efficiency values for 60Hz premium efficiency of motors rated 5000Volts or less
- 20.21.C.3 Addition of 50Hz motors rated 600volts or less
- Table 20-D Addition of full load efficiency values for 50Hz premium efficiency motors 600 volts or less
- 20.25.1 Addition of item I,

< This page is intentionally left blank. >

CONTENTS

	Page No.
Foreword.....	xxxv
Section I GENERAL STANDARDS APPLYING TO ALL MACHINES	
Part 1—REFERENCED STANDARDS AND DEFINITIONS	1-1
1.1 REFERENCED STANDARDS.....	1-1
DEFINITIONS	1-5
CLASSIFICATION ACCORDING TO SIZE	1-5
1.2 MACHINE.....	1-5
1.3 SMALL (FRACTIONAL) MACHINE.....	1-5
1.4 MEDIUM (INTEGRAL) MACHINE.....	1-5
1.4.1 Alternating-Current Medium Machine.....	1-5
1.4.2 Direct-Current Medium Machine.....	1-5
1.5 LARGE MACHINE.....	1-5
1.5.1 Alternating-Current Large Machine.....	1-5
1.5.2 Direct-Current Large Machine.....	1-6
CLASSIFICATION ACCORDING TO APPLICATION	1-6
1.6 GENERAL PURPOSE MOTOR.....	1-6
1.6.1 General-Purpose Alternating-Current Motor.....	1-6
1.6.2 General-Purpose Direct-Current Small Motor.....	1-6
1.7 GENERAL-PURPOSE GENERATOR.....	1-6
1.8 INDUSTRIAL SMALL MOTOR.....	1-6
1.9 INDUSTRIAL DIRECT-CURRENT MEDIUM MOTOR.....	1-6
1.10 INDUSTRIAL DIRECT-CURRENT GENERATOR.....	1-6
1.11 DEFINITE-PURPOSE MOTOR.....	1-7
1.12 GENERAL INDUSTRIAL MOTORS.....	1-7
1.13 METAL ROLLING MILL MOTORS.....	1-7
1.14 REVERSING HOT MILL MOTORS.....	1-7
1.15 SPECIAL-PURPOSE MOTOR.....	1-7
CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	1-8
1.17 GENERAL.....	1-8
1.17.1 Electric Motor.....	1-8
1.17.2 Electric Generator.....	1-8
1.17.3 Electric Machines.....	1-8
1.18 ALTERNATING-CURRENT MOTORS.....	1-9
1.18.1 Induction Motor.....	1-9
1.18.2 Synchronous Motor.....	1-9
1.18.3 Series-Wound Motor.....	1-10
1.19 POLYPHASE MOTORS.....	1-10
1.19.1 Design Letters of Polyphase Squirrel-Cage Medium Motors.....	1-10
1.20 SINGLE-PHASE MOTORS.....	1-10
1.20.1 Design Letters of Single-Phase Small Motors.....	1-10
1.20.2 Design Letters of Single-Phase Medium Motors.....	1-11
1.20.3 Single-Phase Squirrel-Cage Motors.....	1-11
1.20.4 Single-Phase Wound-Rotor Motors.....	1-12
1.21 UNIVERSAL MOTORS.....	1-12
1.21.1 Series-Wound Motor.....	1-12
1.21.2 Compensated Series-Wound Motor.....	1-12
1.22 ALTERNATING-CURRENT GENERATORS.....	1-12
1.22.1 Induction Generator.....	1-12
1.22.2 Synchronous Generator.....	1-13
1.23 DIRECT-CURRENT MOTORS.....	1-13
1.23.1 Shunt-Wound Motor.....	1-13
1.23.2 Series-Wound Motor.....	1-13

1.23.3	Compound-Wound Motor	1-13
1.23.4	Permanent Magnet Motor	1-13
1.24	DIRECT-CURRENT GENERATORS	1-13
1.24.1	Shunt-Wound Generator.....	1-13
1.24.2	Compound-Wound Generator	1-13
CLASSIFICATION ACCORDING TO ENVIRONMENTAL PROTECTION AND METHODS OF COOLING		
1.25	OPEN MACHINE (IP00, IC01).....	1-14
1.25.1	Drip-proof Machine (IP12, IC01)	1-14
1.25.2	Splash-Proof Machine (IP13, IC01)	1-14
1.25.3	Semi-Guarded Machine (IC01)	1-14
1.25.4	Guarded Machine (IC01)	1-14
1.25.5	Drip-proof Guarded Machine (IC01)	1-17
1.25.6	Open Independently Ventilated Machine (IC06).....	1-17
1.25.7	Open Pipe-Ventilated Machine	1-17
1.25.8	Weather-Protected Machine	1-17
1.26	TOTALLY ENCLOSED MACHINE	1-17
1.26.1	Totally Enclosed Nonventilated Machine (IC410).....	1-17
1.26.2	Totally Enclosed Fan-Cooled Machine	1-17
1.26.3	Totally Enclosed Fan-Cooled Guarded Machine (IC411).....	1-18
1.26.4	Totally Enclosed Pipe-Ventilated Machine (IP44)	1-18
1.26.5	Totally Enclosed Water-Cooled Machine (IP54).....	1-18
1.26.6	Water-Proof Machine (IP55)	1-18
1.26.7	Totally Enclosed Air-to-Water-Cooled Machine (IP54).....	1-18
1.26.8	Totally Enclosed Air-to-Air-Cooled Machine (IP54)	1-18
1.26.9	Totally Enclosed Air-Over Machine (IP54, IC417).....	1-18
1.26.10	Explosion-Proof Machine	1-19
1.26.11	Dust-Ignition-Proof Machine	1-19
1.27	MACHINE WITH ENCAPSULATED OR SEALED WINDINGS.....	1-19
1.27.1	Machine with Moisture Resistant Windings	1-19
1.27.2	Machine with Sealed Windings.....	1-19
CLASSIFICATION ACCORDING TO VARIABILITY OF SPEED		
1.30	CONSTANT-SPEED MOTOR	1-19
1.31	VARYING-SPEED MOTOR.....	1-19
1.32	ADJUSTABLE-SPEED MOTOR.....	1-20
1.33	BASE SPEED OF AN ADJUSTABLE-SPEED MOTOR.....	1-20
1.34	ADJUSTABLE VARYING-SPEED MOTOR.....	1-20
1.35	MULTISPEED MOTOR.....	1-20
RATING, PERFORMANCE, AND TEST		
1.40	RATING OF A MACHINE	1-20
1.40.1	Continuous Rating	1-20
1.40.2	Short-Time Rating.....	1-20
1.41	EFFICIENCY.....	1-20
1.41.1	General	1-20
1.41.2	Energy Efficient Polyphase Squirrel-Cage Induction Motor	1-20
1.41.3	Premium Efficiency Motor.....	1-21
1.42	SERVICE FACTOR—AC MOTORS.....	1-21
1.43	SPEED REGULATION OF DC MOTORS	1-21
1.43.1	Percent Compounding of Direct-Current Machines.....	1-21
1.44	VOLTAGE REGULATION OF DIRECT-CURRENT GENERATORS.....	1-21
1.45	SECONDARY VOLTAGE OF WOUND-MOTOR ROTORS.....	1-21
1.46	FULL-LOAD TORQUE.....	1-21
1.47	LOCKED-ROTOR TORQUE (STATIC TORQUE).....	1-21
1.48	PULL-UP TORQUE	1-21
1.49	PUSHOVER TORQUE	1-21
1.50	BREAKDOWN TORQUE.....	1-22

1.51	PULL-OUT TORQUE	1-22
1.52	PULL-IN TORQUE	1-22
1.53	LOCKED-ROTOR CURRENT	1-22
1.54	NO-LOAD CURRENT	1-22
1.55	TEMPERATURE TESTS	1-22
1.56	AMBIENT TEMPERATURE	1-22
1.57	HIGH-POTENTIAL TESTS	1-22
1.58	STARTING CAPACITANCE FOR A CAPACITOR MOTOR	1-22
1.59	RADIAL MAGNETIC PULL AND AXIAL CENTERING FORCE	1-23
	1.59.1 Radial Magnetic Pull	1-23
	1.59.2 Axial Centering Force	1-23
1.60	INDUCTION MOTOR TIME CONSTANTS.....	1-23
	1.60.1 General	1-23
	1.60.2 Open-Circuit AC Time Constant	1-23
	1.60.3 Short-Circuit AC Time Constant	1-23
	1.60.4 Short-Circuit DC Time Constant	1-23
	1.60.5 X/R Ratio.....	1-23
	1.60.6 Definitions (See Figure 1-4).....	1-23
	COMPLETE MACHINES AND PARTS.....	1-24
1.61	SYNCHRONOUS GENERATOR—COMPLETE	1-24
	1.61.1 Belted Type.....	1-24
	1.61.2 Engine Type.....	1-24
	1.61.3 Coupled Type.....	1-24
1.62	DIRECT-CURRENT GENERATOR—COMPLETE	1-24
	1.62.1 Belted Type.....	1-24
	1.62.2 Engine Type.....	1-24
	1.62.3 Coupled Type.....	1-24
1.63	FACE AND FLANGE MOUNTING.....	1-25
	1.63.1 Type C Face	1-25
	1.63.2 Type D Flange	1-25
	1.63.3 Type P Flange.....	1-25
	CLASSIFICATION OF INSULATION SYSTEMS	1-25
1.65	INSULATION SYSTEM DEFINED.....	1-25
	1.65.1 Coil Insulation with its Accessories.....	1-25
	1.65.2 Connection and Winding Support Insulation	1-25
	1.65.3 Associated Structural Parts	1-25
1.66	CLASSIFICATION OF INSULATION SYSTEMS	1-25
	MISCELLANEOUS.....	1-26
1.70	NAMEPLATE MARKING	1-26
	1.70.1 Nameplate.....	1-26
	1.70.2 Additional Nameplate Markings	1-26
1.71	CODE LETTER.....	1-27
1.72	THERMAL PROTECTOR	1-27
1.73	THERMALLY PROTECTED	1-27
1.74	OVER TEMPERATURE PROTECTION.....	1-27
1.75	PART-WINDING START MOTOR.....	1-27
1.76	STAR (WYE) START, DELTA RUN MOTOR	1-27
1.77	CONSTANT FLUX.....	1-27
1.78	DEVIATION FACTOR.....	1-28
1.79	MARKING ABBREVIATIONS FOR MACHINES	1-28

Section I GENERAL STANDARDS APPLYING TO ALL MACHINES

Part 2—TERMINAL MARKINGS

GENERAL.....	2-1
2.1 LOCATION OF TERMINAL MARKINGS	2-1
2.2 TERMINAL MARKINGS.....	2-1

2.3 DIRECTION OF ROTATION2-2

 2.3.1 Alternating-Current Machines2-2

 2.3.2 Direct-Current Machines2-2

 2.3.3 Motor-Generator Sets2-2

DC MOTORS AND GENERATORS.....2-2

2.10 TERMINAL MARKINGS.....2-2

 2.10.1 General2-2

 2.10.2 Armature Leads2-2

 2.10.3 Armature Leads—Direction of Rotation2-2

2.11 TERMINAL MARKINGS FOR DUAL VOLTAGE SHUNT FIELDS2-2

2.12 DIRECTION OF ROTATION2-3

 2.12.1 Direct-Current Motors2-3

 2.12.2 Direct-Current Generators2-3

 2.12.3 Reverse Function.....2-3

2.13 CONNECTION DIAGRAMS WITH TERMINAL MARKINGS FOR DIRECT-CURRENT MOTORS2-3

2.14 CONNECTION DIAGRAMS WITH TERMINAL MARKINGS FOR DIRECT-CURRENT GENERATORS2-7

AC MOTORS AND GENERATORS.....2-9

2.20 NUMERALS ON TERMINALS OF ALTERNATING-CURRENT POLYPHASE MACHINES2-9

 2.20.1 Synchronous Machines2-9

 2.20.2 Induction Machines.....2-9

2.21 DEFINITION OF PHASE SEQUENCE2-9

2.22 PHASE SEQUENCE.....2-9

2.23 DIRECTION OF ROTATION OF PHASORS2-9

2.24 DIRECTION OF ROTATION2-10

AC GENERATORS AND SYNCHRONOUS MOTORS2-10

2.25 REVERSAL OF ROTATION, POLARITY AND PHASE SEQUENCE2-10

2.30 CONNECTION AND TERMINAL MARKINGS—ALTERNATING-CURRENT GENERATORS AND SYNCHRONOUS MOTORS—THREE-PHASE AND SINGLE-PHASE2-10

SINGLE PHASE MOTORS2-11

2.40 GENERAL2-11

 2.40.1 Dual Voltage2-11

 2.40.2 Single Voltage.....2-11

2.41 TERMINAL MARKINGS IDENTIFIED BY COLOR.....2-12

2.42 AUXILIARY DEVICES WITHIN MOTOR2-12

2.43 AUXILIARY DEVICES EXTERNAL TO MOTOR.....2-12

2.44 MARKING OF RIGIDLY MOUNTED TERMINALS.....2-12

2.45 INTERNAL AUXILIARY DEVICES PERMANENTLY CONNECTED TO RIGIDLY MOUNTED TERMINALS.....2-13

2.46 GENERAL PRINCIPLES FOR TERMINAL MARKINGS FOR SINGLE-PHASE MOTORS2-13

 2.46.1 First Principle2-13

 2.46.2 Second Principle2-13

 2.46.3 Third Principle2-13

2.47 SCHEMATIC DIAGRAMS FOR SPLIT-PHASE MOTORS—SINGLE VOLTAGE—REVERSIBLE2-14

 2.47.1 Without Thermal Protector2-14

 2.47.2 With Thermal Protector2-14

2.48 SCHEMATIC DIAGRAMS FOR CAPACITOR-START MOTORS—REVERSIBLE2-15

 2.48.1 Single-Voltage Capacitor-start Motors—Reversible2-15

 2.48.2 Dual-Voltage Capacitor-start Motors—Reversible.....2-16

2.49	SCHEMATIC DIAGRAMS FOR TWO-VALUE CAPACITOR MOTORS—SINGLE VOLTAGE—REVERSIBLE	2-20
	2.49.1 Without Thermal Protector	2-20
	2.49.2 With Thermal Protector	2-21
2.50	SCHEMATIC DIAGRAMS FOR PERMANENT-SPLIT CAPACITOR MOTORS—SINGLE VOLTAGE—REVERSIBLE	2-22
2.51	SCHEMATIC DIAGRAMS FOR UNIVERSAL MOTORS—SINGLE VOLTAGE	2-23
2.52	SCHEMATIC DIAGRAMS FOR REPULSION, REPULSION-START INDUCTION, AND REPULSION-INDUCTION MOTORS	2-24
2.53	SHADED-POLE MOTORS—TWO SPEED	2-25
2.60	GENERAL PRINCIPLES FOR TERMINAL MARKINGS FOR POLYPHASE INDUCTION MOTORS	2-25
	2.60.1 Method of Marking	2-25
	2.60.2 Three-Phase, Two Speed Motors	2-27
	2.60.3 Two-Phase Motors	2-27
2.61	TERMINAL MARKINGS FOR THREE-PHASE SINGLE-SPEED INDUCTION MOTORS	2-27
	2.61.1 First	2-27
	2.61.2 Second	2-27
	2.61.3 Third	2-27
	2.61.4 Fourth	2-27
	2.61.5 Fifth	2-27
	2.61.6 Sixth	2-28
2.62	TERMINAL MARKINGS FOR Y- AND DELTA-CONNECTED DUAL VOLTAGE MOTORS	2-28
2.63	TERMINAL MARKINGS FOR THREE-PHASE TWO-SPEED SINGLE-WINDING INDUCTION MOTORS	2-28
2.64	TERMINAL MARKINGS FOR Y- AND DELTA-CONNECTED THREE-PHASE TWO-SPEED SINGLE-WINDING MOTORS	2-28
2.65	TERMINAL MARKINGS FOR THREE-PHASE INDUCTION MOTORS HAVING TWO OR MORE SYNCHRONOUS SPEEDS OBTAINED FROM TWO OR MORE INDEPENDENT WINDINGS	2-34
	2.65.1 Each Independent Winding Giving One Speed	2-34
	2.65.2 Each Independent Winding Reconnectible to Give Two Synchronous Speeds	2-34
	2.65.3 Two or More Independent Windings at Least One of Which Gives One Synchronous Speed and the Other Winding Gives Two Synchronous Speeds	2-35
2.66	TERMINAL MARKINGS OF THE ROTORS OF WOUND-ROTOR INDUCTION MOTORS	2-38
2.67	TERMINAL MARKINGS	2-38

Section I GENERAL STANDARDS APPLYING TO ALL MACHINES

Part 3—HIGH-POTENTIAL TESTS

3.1	HIGH-POTENTIAL TESTS	3-1
	3.1.1 Safety	3-1
	3.1.2 Definition	3-1
	3.1.3 Procedure	3-1
	3.1.4 Test Voltage	3-1
	3.1.5 Condition of Machine to be Tested	3-1
	3.1.6 Duration of Application of Test Voltage	3-1
	3.1.7 Points of Application of Test Voltage	3-2
	3.1.8 Accessories and Components	3-2
	3.1.9 Evaluation of Dielectric Failure	3-2
	3.1.10 Initial Test at Destination	3-2

3.1.11 Tests of an Assembled Group of Machines and Apparatus3-2
 3.1.12 Additional Tests Made After Installation3-3

Section I GENERAL STANDARDS APPLYING TO ALL MACHINES

Part 4—DIMENSIONS, TOLERANCES, AND MOUNTING

4.1 LETTERING OF DIMENSION SHEETS.....4-1
 4.2 SYSTEM FOR DESIGNATING FRAMES.....4-10
 4.2.1 Frame Numbers4-10
 4.2.2 Frame Letters.....4-11
 4.3 MOTOR MOUNTING AND TERMINAL HOUSING LOCATION.....4-12
 4.4 DIMENSIONS—AC MACHINES4-14
 4.4.1 Dimensions for Alternating-Current Foot-Mounted
 Machines with Single Straight-Shaft Extension4-14
 4.4.2 Shaft Extensions and Key Dimensions for Alternating-
 Current Foot-Mounted Machines with Single Tapered or
 Double Straight/Tapered Shaft Extension4-16
 4.4.3 Shaft Extension Diameters and Key Dimensions for
 Alternating-Current Motors Built in Frames Larger than the 449T Frames4-17
 4.4.4 Dimensions for Type C Face-Mounting Foot or Footless
 Alternating-Current Motors.....4-17
 4.4.5 Dimensions for Type FC Face Mounting for Accessories
 on End of Alternating-Current Motors4-18
 4.4.6 Dimensions for Type D Flange-Mounting Foot or Footless
 Alternating-Current Motors.....4-19
 4.5 DIMENSIONS—DC MACHINES4-20
 4.5.1 Dimensions for Direct-Current Small Motors with
 Single Straight Shaft Extension4-20
 4.5.2 Dimensions for Foot-Mounted Industrial Direct-Current Machines4-21
 4.5.3 Dimensions for Foot-Mounted Industrial Direct-Current Motors4-25
 4.5.4 Dimensions for Type C Face-Mounting Direct-Current
 Small Motors4-26
 4.5.5 Dimensions for Type C Face-Mounting Industrial Direct-Current Motors.....4-26
 4.5.6 Dimensions for Type C Face-Mounting Industrial Direct-Current Motors.....4-27
 4.5.7 Dimensions for Type D Flange-Mounting Industrial Direct-Current Motors.....4-27
 4.5.8 Base Dimensions for Type P and PH Vertical Solid-Shaft
 Industrial Direct-Current Motors4-28
 4.5.9 Dimensions for Type FC Face Mounting for Accessories
 on End Opposite Drive End of Industrial Direct-Current Motors4-28
 4.6 SHAFT EXTENSION DIAMETERS FOR UNIVERSAL MOTORS4-28
 4.7 TOLERANCE LIMITS IN DIMENSIONS.....4-29
 4.8 KNOCKOUT AND CLEARANCE HOLE DIAMETER FOR MACHINE
 TERMINAL BOXES4-29
 4.9 TOLERANCES ON SHAFT EXTENSION DIAMETERS AND
 KEYSEATS4-29
 4.9.1 Shaft Extension Diameter4-29
 4.9.2 Keyseat Width.....4-29
 4.9.3 Bottom of Keyseat to Shaft Surface.....4-29
 4.9.4 Parallelism of Keyseats to Shaft Centerline4-30
 4.9.5 Lateral Displacement of Keyseats4-30
 4.9.6 Diameters and Keyseat Dimensions.....4-30
 4.9.7 Shaft Runout4-30
 4.9.8 Shaft Extension Key(s)4-31
 4.10 RING GROOVE SHAFT KEYSEATS FOR VERTICAL SHAFT MOTORS4-32
 4.11 METHOD OF MEASUREMENT OF SHAFT RUNOUT AND OF
 ELECTRICITY AND FACE RUNOUT OF MOUNTING SURFACES4-32
 4.11.1 Shaft Runout4-32

	4.11.2 Eccentricity and Face Runout of Mounting Surfaces.....	4-32
4.12	TOLERANCES FOR TYPE C FACE MOUNTING AND TYPE D FLANGE MOUNTING MOTORS	4-33
4.13	TOLERANCES FOR TYPE P FLANGE-MOUNTING MOTORS.....	4-33
4.14	MOUNTING BOLTS OR STUDS.....	4-33
4.15	METHOD TO CHECK COPLANARITY OF FEET OF FULLY ASSEMBLED MOTORS.....	4-34
4.16	METHOD OF MEASUREMENT OF SHAFT EXTENSION PARALLELISM TO FOOT PLANE	4-34
4.17	MEASUREMENT OF BEARING TEMPERATURE	4-34
4.18	TERMINAL CONNECTIONS FOR SMALL MOTORS.....	4-35
	4.18.1 Terminal Leads	4-35
	4.18.2 Blade Terminals.....	4-35
4.19	MOTOR TERMINAL HOUSINGS	4-35
	4.19.1 Small and Medium Motors	4-35
	4.19.2 Dimensions	4-35
4.20	GROUNDING MEANS FOR FIELD WIRING	4-41

Section I GENERAL STANDARDS APPLYING TO ALL MACHINES

Part 5—ROTATING ELECTRICAL MACHINES—CLASSIFICATION OF DEGREES OF PROTECTION PROVIDED BY ENCLOSURES FOR ROTATING MACHINES

5.1	SCOPE	5-1
5.2	DESIGNATION	5-1
	5.2.1 Single Characteristic Numeral	5-1
	5.2.2 Supplementary Letters.....	5-1
	5.2.3 Example of Designation.....	5-2
	5.2.4 Most Frequently Used.....	5-2
5.3	DEGREES OF PROTECTION—FIRST CHARACTERISTIC NUMERAL	5-2
	5.3.1 Indication of Degree of Protection	5-2
	5.3.2 Compliance to Indicated Degree of Protection	5-2
	5.3.3 External Fans.....	5-2
	5.3.4 Drain Holes	5-3
	Table 5-1	5-3
5.4	DEGREES OF PROTECTION—SECOND CHARACTERISTIC NUMERAL	5-4
	5.4.1 Indication of Degree of Protection	5-4
	5.4.2 Compliance to Indicated Degree of Protection	5-4
	Table 5-2	5-4
5.5	MARKING	5-5
5.6	GENERAL REQUIREMENTS FOR TESTS	5-5
	5.6.1 Adequate Clearance	5-5
5.7	TESTS FOR FIRST CHARACTERISTIC NUMERAL	5-5
	Table 5-3	5-6
5.8	TESTS FOR SECOND CHARACTERISTIC NUMERAL.....	5-7
	5.8.1 Test Conditions	5-7
	Table 5-4.....	5-8
	5.8.2 Acceptance Conditions	5-10
	5.8.3 Allowable Water Leakage.....	5-10
5.9	REQUIREMENTS AND TESTS FOR OPEN WEATHER-PROTECTED MACHINES	5-10
	Figure 5-1	5-11
	Figure 5-2	5-12
	Figure 5-3	5-13
	Figure 5-4	5-14
	Figure 5-5	5-15
	Figure 5-6	5-16

Section I GENERAL STANDARDS APPLYING TO ALL MACHINES

Part 6—ROTATING ELECTRICAL MACHINES—METHODS OF COOLING (IC CODE)

6.1	SCOPE	6-1
6.2	DEFINITIONS	6-1
	6.2.1 Cooling	6-1
	6.2.2 Coolant.....	6-1
	6.2.3 Primary Coolant	6-1
	6.2.4 Secondary Coolant	6-1
	6.2.5 Final Coolant.....	6-1
	6.2.6 Surrounding Medium	6-1
	6.2.7 Remote Medium.....	6-2
	6.2.8 Direct Cooled Winding (Inner-cooled Winding)	6-2
	6.2.9 Indirect Cooled Winding.....	6-2
	6.2.10 Heat Exchange	6-2
	6.2.11 Pipe, Duct	6-2
	6.2.12 Open Circuit.....	6-2
	6.2.13 Closed Circuit.....	6-2
	6.2.14 Piped or Ducted Circuit.....	6-2
	6.2.15 Stand-by or Emergency Cooling System.....	6-2
	6.2.16 Integral Component	6-2
	6.2.17 Machine-Mounted Component	6-3
	6.2.18 Separate Component.....	6-3
	6.2.19 Dependent Circulation Component	6-3
	6.2.20 Independent Circulation Component	6-3
6.3	DESIGNATION SYSTEM	6-3
	6.3.1 Arrangement of the IC Code.....	6-3
	6.3.2 Application of Designations	6-4
	6.3.3 Designation of Same Circuit Arrangements for Different Parts of a Machine	6-4
	6.3.4 Designation of Different Circuit Arrangements for Different Parts of a Machine	6-4
	6.3.5 Designation of Direct Cooled Winding	6-5
	6.3.6 Designation of Stand-by or Emergency Cooling Conditions	6-5
	6.3.7 Combined Designations.....	6-5
	6.3.8 Replacement of Characteristic Numerals	6-5
6.4	CHARACTERISTIC NUMERAL FOR CIRCUIT ARRANGEMENT	6-5
6.5	CHARACTERISTIC LETTERS FOR COOLANT	6-6
6.6	CHARACTERISTIC NUMERAL FOR METHOD OF MOVEMENT	6-7
6.7	COMMONLY USED DESIGNATIONS	6-8
	6.7.1 General Information on the Tables	6-8

Section I GENERAL STANDARDS APPLYING TO ALL MACHINES

Part 7—MECHANICAL VIBRATION-MEASUREMENT, EVALUATION AND LIMITS

7.1	SCOPE	7-1
7.2	OBJECT	7-1
7.3	REFERENCES	7-1
7.4	MEASUREMENT QUANTITY.....	7-1
	7.4.1 Bearing Housing Vibration	7-1
	7.4.2 Relative Shaft Vibration	7-1
7.5	MEASURING EQUIPMENT.....	7-1
7.6	MACHINE MOUNTING.....	7-2
	7.6.1 General	7-2
	7.6.2 Resilient Mounting	7-2
	7.6.3 Rigid Mounting	7-2
	7.6.4 Active Environment Determination	7-3

7.7	CONDITIONS OF MEASUREMENT	7-3
	7.7.1 Shaft Key	7-3
	7.7.2 Measurement Points for Vibration	7-3
	7.7.3 Operating Conditions	7-4
	7.7.4 Vibration Transducer Mounting.....	7-4
7.8	LIMITS OF BEARING HOUSING VIBRATION.....	7-7
	7.8.1 General	7-7
	7.8.5 Twice Line Frequency Vibration of Two Pole Induction Machines	7-9
	7.8.6 Axial Vibration	7-10
7.9	LIMITS OF RELATIVE SHAFT VIBRATION.....	7-10
	7.9.1 General	7-10
	7.9.2 Shaft Vibration Limits.....	7-10
	7.9.3 Special Machines.....	7-10

Section I GENERAL STANDARDS APPLYING TO ALL MACHINES

Part 9—ROTATING ELECTRICAL MACHINES—SOUND POWER LIMITS AND MEASUREMENT PROCEDURES

9.1	SCOPE	9-1
9.2	GENERAL.....	9-1
9.3	REFERENCES	9-1
9.4	METHODS OF MEASUREMENT	9-1
9.5	TEST CONDITIONS	9-2
	9.5.1 Machine Mounting	9-2
	9.5.2 Test Operating Conditions	9-2
9.6	SOUND POWER LEVEL	9-2
9.7	DETERMINATION OF SOUND PRESSURE LEVEL.....	9-3
	Table 9-1	9-4
	Table 9-2.....	9-5
	Table 9-3.....	9-5
	Table 9-4.....	9-6

Section II SMALL (FRACTIONAL) AND MEDIUM (INTEGRAL) MACHINES

Part 10—AC SMALL AND MEDIUM MOTORS

10.0	SCOPE	10-1
10.30	VOLTAGES.....	10-1
10.31	FREQUENCIES	10-1
	10.31.1 Alternating-Current Motors	10-1
	10.31.2 Universal Motors.....	10-1
10.32	HORSEPOWER AND SPEED RATINGS.....	10-2
	10.32.1 Small Induction Motors, Except Permanent-Split Capacitor Motors Rated 1/3 Horsepower and Smaller and Shaded- Pole Motors	10-2
	10.32.2 Small induction Motors, permanent-Split Capacitor Motors Rated 1/3 Horsepower and Smaller and Shaded-Pole Motors.....	10-2
	10.32.3 Single-Phase Medium Motors.....	10-3
	10.32.4 Polyphase Medium Induction Motors	10-3
	10.32.5 Universal Motors	10-4
10.33	HORSEPOWER RATINGS OF MULTISPEED MOTORS	10-4
	10.33.1 Constant Horsepower	10-4
	10.33.2 Constant Torque	10-5
	10.33.3 Variable Torque	10-5
10.34	BASIS FOR HORSEPOWER RATING.....	10-5
	10.34.1 Basis of Rating.....	10-5
	10.34.2 Temperature	10-5
	10.34.3 Minimum Breakdown Torque.....	10-5
10.35	SECONDARY DATA FOR WOUND-ROTOR-MOTORS	10-8

10.36 TIME RATINGS FOR SINGLE-PHASE AND POLYPHASE
INDUCTION MOTORS 10-8

10.37 CODE LETTERS (FOR LOCKED-ROTOR KVA) 10-8

 10.37.1 Nameplate Marking 10-8

 10.37.2 Letter Designation 10-8

 10.37.3 Multispeed Motors 10-8

 10.37.4 Single-Speed Motors 10-9

 10.37.5 Broad- or Dual-Voltage Motors 10-9

 10.37.6 Dual-Frequency Motors 10-9

 10.37.7 Part-Winding-Start Motors 10-9

10.38 NAMEPLATE TEMPERATURE RATINGS FOR ALTERNATING-
CURRENT SMALL AND UNIVERSAL MOTORS 10-9

10.39 NAMEPLATE MARKING FOR ALTERNATING-CURRENT SMALL
AND UNIVERSAL MOTORS 10-9

 10.39.1 Alternating-Current Single-Phase and Polyphase Squirrel-
 Cage Motors, Except Those Included in 10.39.2, 10.39.3,
 and 10.39.4 10-9

 10.39.2 Motors Rated Less than 1/20 Horsepower 10-10

 10.39.3 Universal Motors 10-10

 10.39.4 Motors Intended for Assembly in a Device Having its
 Own Markings 10-10

 10.39.5 Motors for Dual Voltage 10-10

10.40 NAMEPLATE MARKING FOR MEDIUM SINGLE-PHASE AND
POLYPHASE INDUCTION MOTORS 10-11

 10.40.1 Medium Single-Phase and Polyphase Squirrel-Cage Motors 10-11

 10.40.2 Polyphase Wound-Rotor Motors 10-12

Section II SMALL (FRACTIONAL) AND MEDIUM (INTEGRAL) MACHINES

Part 10—DC SMALL AND MEDIUM MOTORS

10.0 SCOPE 10-13

10.60 BASIS OF RATING 10-13

 10.60.1 Small Motors 10-13

 10.60.2 Medium Motors 10-13

10.61 POWER SUPPLY IDENTIFICATION FOR DIRECT-CURRENT
MEDIUM MOTORS 10-13

 10.60.1 Supplies Designated by a Single Letter 10-13

 10.60.2 Other Supply Types 10-13

10.62 HORSEPOWER, SPEED, AND VOLTAGE RATINGS 10-14

 10.62.1 Direct-Current Small Motors 10-14

 10.62.2 Industrial Direct-Current Motors 10-15

10.63 NAMEPLATE TIME RATING 10-15

10.64 TIME RATING FOR INTERMITTENT, PERIODIC, AND VARYING
DUTY 10-15

10.65 NAMEPLATE MAXIMUM AMBIENT TEMPERATURE AND
INSULATION SYSTEM CLASS 10-15

10.66 NAMEPLATE MARKING 10-17

 10.66.1 Small Motors Rated 1/20 Horsepower and Less 10-17

 10.66.2 Small Motors Except Those Rated 1/20 Horsepower and
 Less 10-18

 10.66.3 Medium Motors 10-18

Section II SMALL (FRACTIONAL) AND MEDIUM (INTEGRAL) MACHINES

Part 12—TESTS AND PERFORMANCE—AC AND DC MOTORS

12.0	SCOPE	12-1
12.2	HIGH-POTENTIAL TEST—SAFETY PRECAUTIONS AND TEST PROCEDURE	12-1
12.3	HIGH-POTENTIAL TEST VOLTAGES FOR UNIVERSAL, INDUCTION, AND DIRECT-CURRENT MOTORS	12-1
12.4	PRODUCTION HIGH-POTENTIAL TESTING OF SMALL MOTORS.....	12-2
	12.4.1 Dielectric Test Equipment.....	12-3
	12.4.2 Evaluation of Insulation Systems by a Dielectric Test.....	12-3
12.5	REPETITIVE SURGE TEST FOR SMALL AND MEDIUM MOTORS	12-3
12.6	MECHANICAL VIBRATION.....	12-4
12.7	BEARING LOSSES—VERTICAL PUMP MOTORS.....	12-4

Section II SMALL (FRACTIONAL) AND MEDIUM (INTEGRAL) MACHINES

Part 12—TESTS AND PERFORMANCE—AC MOTORS

12.0	SCOPE	12-5
12.30	TEST METHODS.....	12-5
12.31	PERFORMANCE CHARACTERISTICS.....	12-5
12.32	TORQUE CHARACTERISTICS OF SINGLE-PHASE GENERAL- PURPOSE INDUCTION MOTORS	12-5
	12.32.1 Breakdown Torque	12-5
	12.32.2 Locked-rotor Torque of Small Motors	12-6
	12.32.3 Locked-rotor Torque of Medium Motors	12-6
	12.32.4 Pull-Up Torque of Medium Motors.....	12-6
12.33	LOCKED-ROTOR CURRENT OF SINGLE-PHASE SMALL MOTORS.....	12-6
	12.33.1 Design O and Design N Motors	12-6
	12.33.2 General-Purpose Motors	12-7
12.34	LOCKED-ROTOR CURRENT OF SINGLE-PHASE MEDIUM MOTORS, DESIGNS L AND M	12-7
12.35	LOCKED-ROTOR CURRENT OF 3-PHASE 60-HERTZ SMALL AND MEDIUM SQUIRREL-CAGE INDUCTION MOTORS RATED AT 230 VOLTS	12-7
	12.35.1 60-Hertz Design B, C, and D Motors at 230 Volts	12-7
	12.35.2 50-Hertz Design B, C, and D Motors at 380 Volts	12-9
12.36	INSTANTANEOUS PEAK VALUE OF INRUSH CURRENT	12-9
12.37	TORQUE CHARACTERISTICS OF POLYPHASE SMALL MOTORS.....	12-9
12.38	LOCKED-ROTOR TORQUE OF SINGLE-SPEED POLYPHASE SQUIRREL-CAGE MEDIUM MOTORS WITH CONTINUOUS RATINGS	12-10
	12.38.1 Design A and B Motors.....	12-10
	12.38.2 Design C Motors	12-10
	12.38.3 Design D Motors	12-11
12.39	BREAKDOWN TORQUE OF SINGLE-SPEED POLYPHASE SQUIRREL-CAGE MEDIUM MOTORS WITH CONTINUOUS RATINGS	12-11
	12.39.1 Design A and B Motors.....	12-11
	12.39.2 Design C Motors	12-11
12.40	PULL-UP TORQUE OF SINGLE-SPEED POLYPHASE SQUIRREL- CAGE MEDIUM MOTORS WITH CONTINUOUS RATINGS.....	12-12
	12.40.1 Design A and B Motors.....	12-12
	12.40.2 Design C Motors	12-13
12.41	BREAKDOWN TORQUE OF POLYPHASE WOUND-ROTOR MEDIUM MOTORS WITH CONTINUOUS RATINGS.....	12-13
12.42	TEMPERATURE RISE FOR SMALL AND UNIVERSAL MOTORS.....	12-14

12.42.1	Alternating-Current Small Motors—Motor Nameplates Marked with Insulation System Designation and Ambient Temperature.....	12-14
12.42.2	Universal Motors.....	12-15
12.42.3	Temperature Rise for Ambients Higher than 40°C.....	12-15
12.42.4	Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C but Not Below 0° C.....	12-16
12.43	TEMPERATURE RISE FOR MEDIUM SINGLE-PHASE AND POLYPHASE INDUCTION MOTORS.....	12-17
12.43.1	Temperature Rise for Ambients Higher than 40°C.....	12-17
12.43.2	Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C.....	12-18
12.44	VARIATION FROM RATED VOLTAGE AND RATED FREQUENCY.....	12-19
12.44.1	Running.....	12-19
12.44.2	Starting.....	12-19
12.45	VOLTAGE UNBALANCE.....	12-19
12.46	VARIATION FROM RATED SPEED.....	12-19
12.47	NAMEPLATE AMPERES—ALTERNATING-CURRENT MEDIUM MOTORS.....	12-19
12.48	OCCASIONAL EXCESS CURRENT.....	12-19
12.49	STALL TIME.....	12-20
12.50	PERFORMANCE OF MEDIUM MOTORS WITH DUAL VOLTAGE RATING (SUGGESTED STANDARD FOR FUTURE DESIGN).....	12-20
12.51	SERVICE FACTOR OF ALTERNATING-CURRENT MOTORS.....	12-20
12.51.1	General-Purpose Alternating-Current Motors of the Open Type.....	12-20
12.51.2	Other Motors.....	12-21
12.52	OVERSPEEDS FOR MOTORS.....	12-21
12.52.1	Squirrel-Cage and Wound-Rotor Motors.....	12-21
12.52.2	General-Purpose Squirrel-Cage Induction Motors.....	12-21
12.52.3	General-Purpose Design A and B Direct-Coupled Drive Squirrel-Cage Induction Motors.....	12-23
12.52.4	Alternating-Current Series and Universal Motors.....	12-23
12.53	MACHINE SOUND (MEDIUM INDUCTION MOTORS).....	12-25
12.54	NUMBER OF STARTS.....	12-25
12.54.1	Normal Starting Conditions.....	12-25
12.54.2	Other than Normal Starting Conditions.....	12-25
12.54.3	Considerations for Additional Starts.....	12-25
12.55	ROUTINE TESTS FOR POLYPHASE MEDIUM INDUCTION MOTORS.....	12-25
12.55.1	Method of Testing.....	12-25
12.55.2	Typical Tests on Completely Assembled Motors.....	12-26
12.55.3	Typical of Tests on Motors Not Completely Assembled.....	12-26
12.56	THERMAL PROTECTION OF MEDIUM MOTORS.....	12-27
12.56.1	Winding Temperature.....	12-27
12.56.2	Trip Current.....	12-29
12.57	OVERTEMPERATURE PROTECTION OF MEDIUM MOTORS NOT MEETING THE DEFINITION OF "THERMALLY PROTECTED".....	12-29
12.57.1	Type 1—Winding Running and Locked Rotor Overtemperature Protection.....	12-29
12.57.2	Type 2—Winding Running Overtemperature Protection.....	12-29
12.57.3	Type 3—Winding Overtemperature Protection, Nonspecific Type.....	12-29
12.58	EFFICIENCY.....	12-29
12.58.1	Determination of Motor Efficiency and Losses.....	12-29
12.58.2	Efficiency of Polyphase Squirrel-Cage Medium Motors with Continuous Ratings.....	12-30
12.59	EFFICIENCY LEVELS OF ENERGY EFFICIENT POLYPHASE SQUIRREL-CAGE INDUCTION MOTORS.....	12-31

12.60	EFFICIENCY LEVEL OF PREMIUM EFFICIENCY ELECTRIC MOTORS.....	12-32
12.60.1	60 Hz Motors Rated 600 Volts or Less (Random Wound)	12-32
12.60.2	60 Hz Motors Rated Medium Voltage, 5000 Volts or Less (Form Wound)	12-32
12.60.3	50 Hz Motors Rated 400 Volts or Less (Random Wound)	12-32
12.61	REPORT OF TEST FOR TESTS ON INDUCTION MOTORS	12-32
	Table 12-11	12-33
	Table 12-12	12-35
	Table 12-13	12-37
	Table 12-14	12-38
12.62	MACHINE WITH ENCAPSULATED OR SEALED WINDING CONFORMANCE TESTS.....	12-40
12.63	MACHINE WITH MOISTURE RESISTANT WINDINGS— CONFORMANCE TEST	12-40

Section II SMALL (FRACTIONAL) AND MEDIUM (INTEGRAL) MACHINES

Part 12—TESTS AND PERFORMANCE—DC SMALL AND MEDIUM MOTORS

12.0	SCOPE	12-41
12.65	TEST METHODS.....	12-41
12.66	TEST POWER SUPPLY	12-41
	12.66.1 Small Motors	12-41
	12.66.2 Medium Motors	12-41
12.67	TEMPERATURE RISE	12-43
	12.67.1 Direct-Current Small Motors	12-43
	12.67.2 Continuous-Time-Rated Direct-Current Medium Motors	12-43
	12.67.3 Short-Time-Rated Direct-Current Medium Motors.....	12-44
	12.67.4 Temperature Rise for Ambients Higher than 40°C	12-44
	12.67.5 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C.....	12-45
12.68	VARIATION FROM RATED VOLTAGE.....	12-46
12.69	VARIATION IN SPEED DUE TO LOAD	12-46
	12.69.1 Straight-Shunt-Wound, Stabilized-Shunt-Wound, and Permanent-Magnet Direct-Current Motors	12-46
	12.69.2 Compound-Wound Direct-Current Motors	12-46
12.70	VARIATION IN BASE SPEED DUE TO HEATING	12-46
	12.70.1 Speed Variation with Temperature	12-46
	12.70.2 Resistance Variation with Temperature.....	12-47
12.71	VARIATION FROM RATED SPEED	12-47
12.72	MOMENTARY OVERLOAD CAPACITY	12-47
12.73	SUCCESSFUL COMMUTATION	12-47
12.74	OVERSPEEDS FOR MOTORS.....	12-47
	12.74.1 Shunt-Wound Motors.....	12-47
	12.74.2 Compound-Wound Motors Having Speed Regulation of 35 Percent or Less	12-47
	12.74.3 Series-Wound Motors and Compound-Wound Motors Having Speed Regulation Greater Than 35 Percent	12-47
12.75	FIELD DATA FOR DIRECT-CURRENT MOTORS	12-48
12.76	ROUTINE TESTS ON MEDIUM DIRECT-CURRENT MOTORS.....	12-48
12.77	REPORT OF TEST FORM FOR DIRECT-CURRENT MACHINES	12-48
12.78	EFFICIENCY.....	12-48
	12.78.1 Type A Power Supplies	12-48
	12.78.2 Other Power Supplies.....	12-49
12.79	STABILITY	12-49
12.80	OVER TEMPERATURE PROTECTION OF MEDIUM DIRECT- CURRENT MOTORS.....	12-49
12.81	DATA FOR DIRECT CURRENT MOTORS.....	12-50
12.82	MACHINE SOUND OF DIRECT-CURRENT MEDIUM MOTORS	12-51

Section II SMALL (FRACTIONAL) AND MEDIUM (INTEGRAL) MACHINES

**Part 13—FRAME ASSIGNMENTS FOR ALTERNATING CURRENT
INTEGRAL HORSEPOWER INDUCTION MOTORS**

13.0 SCOPE 13-1

13.1 FRAME DESIGNATIONS FOR SINGLE-PHASE DESIGN L,
HORIZONTAL, AND VERTICAL MOTORS, 60 HERTZ
CLASS B INSULATION SYSTEM, OPEN TYPE, 1.15
SERVICE FACTOR, 230 VOLTS AND LESS 13-1

13.2 FRAME DESIGNATIONS FOR POLYPHASE, SQUIRREL-CAGE,
DESIGNS A, B, AND E, HORIZONTAL AND VERTICAL MOTORS,
60 HERTZ, CLASS B INSULATION SYSTEM, OPEN TYPE, 1.15
SERVICE FACTOR, 575 VOLTS AND LESS 13-2

13.3 FRAME DESIGNATIONS FOR POLYPHASE, SQUIRREL-CAGE,
DESIGNS A, B, ND E, HORIZONTAL AND VERTICAL MOTORS,
60 HERTZ, CLASS B INSULATION SYSTEM, TOTALLY ENCLOSED
FAN-COOLED TYPE, 1.0 SERVICE FACTOR, 575 VOLTS AND LESS 13-3

13.4 FRAME DESIGNATIONS FOR POLYPHASE, SQUIRREL-CAGE,
DESIGN C, HORIZONTAL AND VERTICAL MOTORS, 60 HERTZ,
CLASS B INSULATION SYSTEM, OPEN TYPE, 1.15 SERVICE
FACTOR, 575 VOLTS AND LESS 13-4

13.5 FRAME DESIGNATIONS FOR POLYPHASE, SQUIRREL-CAGE,
DESIGN C, HORIZONTAL AND VERTICAL MOTORS, 60 HERTZ,
CLASS B INSULATION SYSTEM, TOTALLY ENCLOSED FAN-
COOLED TYPE, 1.0 SERVICE FACTOR, 575 VOLTS AND LESS..... 13-5

SECTION II SMALL (FRACTIONAL) AND MEDIUM (INTEGRAL) MACHINES)

Part 14—APPLICATION DATA—AC AND DC SMALL AND MEDIUM MACHINES

14.0 SCOPE 14-1

14.1 PROPER SELECTION OF APPARATUS 14-1

14.2 USUAL SERVICE CONDITIONS 14-2

 14.2.1 Environmental Conditions 14-2

 14.2.2 Operating Conditions 14-2

14.3 UNUSUAL SERVICE CONDITIONS 14-2

14.4 TEMPERATURE RISE 14-3

 14.4.1 Motors with Class A or Class B Insulation Systems 14-3

 14.4.2 Motors with Service Factor 14-3

 14.4.3 Temperature Rise at Sea Level 14-3

 14.4.4 Preferred Values of Altitude for Rating Motors 14-4

14.5 SHORT-TIME RATED ELECTRICAL MACHINES 14-4

14.6 DIRECTION OF ROTATION 14-4

14.7 APPLICATION OF PULLEYS, SHEAVES, SPROCKETS, AND
GEARS ON MOTOR SHAFTS 14-4

 14.7.1 Mounting 14-4

 14.7.2 Minimum Pitch Diameter for Drives Other than V-Belt 14-4

 14.7.3 Maximum Speed of Drive Components 14-5

14.8 THROUGH-BOLT MOUNTING 14-5

14.9 RODENT PROTECTION 14-5

SECTION II SMALL (FRACTIONAL) AND MEDIUM (INTEGRAL) MACHINES

Part 14—APPLICATION DATA—AC SMALL AND MEDIUM MOTORS

14.0 SCOPE 14-7

14.30 EFFECTS OF VARIATION OF VOLTAGE AND FREQUENCY UPON
THE PERFORMANCE OF INDUCTION MOTORS..... 14-7

 14.30.1 General 14-7

 14.30.2 Effects of Variation in Voltage on Temperature..... 14-7

14.30.3	Effect of Variation in Voltage on Power Factor	14-7
14.30.4	Effect of Variation in Voltage on Starting Torques.....	14-7
14.30.5	Effect of Variation in Voltage on Slip	14-7
14.30.6	Effects of Variation in Frequency.....	14-8
14.30.7	Effect of Variations in Both Voltage and Frequency	14-8
14.30.8	Effect on Special-Purpose or Small Motors	14-8
14.31	MACHINES OPERATING ON AN UNDERGROUND SYSTEM	14-8
14.32	OPERATION OF ALTERNATING CURRENT MOTORS FROM VARIABLE-FREQUENCY OR VARIABLE-VOLTAGE POWER SUPPLIES, OR BOTH	14-8
14.32.1	Performance	14-8
14.32.2	Shaft Voltages.....	14-9
14.33	EFFECTS OF VOLTAGES OVER 600 VOLTS ON THE PERFORMANCE OF LOW-VOLTAGE MOTORS.....	14-9
14.34	OPERATION OF GENERAL-PURPOSE ALTERNATING-CURRENT POLYPHASE, 2-, 4-, 6-, AND 8-POLE, 60-HERTZ MEDIUM INDUCTION MOTORS OPERATED ON 50 HERTZ.....	14-9
14.34.1	Speed.....	14-9
14.34.2	Torques.....	14-9
14.34.3	Locked-Rotor Current	14-10
14.34.4	Service Factor	14-10
14.34.5	Temperature Rise	14-10
14.35	OPERATION OF 230-VOLT INDUCTION MOTORS ON 208-VOLT SYSTEMS.....	14-10
14.35.1	General	14-10
14.35.2	Nameplate Marking of Useable @ 200 V	14-10
14.35.3	Effect on Performance of Motor	14-10
14.36	EFFECTS OF UNBALANCED VOLTAGES ON THE PERFORMANCE OF POLYPHASE INDUCTION MOTORS	14-10
14.36.1	Effect on Performance—General.....	14-11
14.36.2	Unbalance Defined	14-11
14.36.3	Torques.....	14-11
14.36.4	Full-Load Speed	14-11
14.36.5	Currents	14-11
14.37	APPLICATION OF ALTERNATING-CURRENT MOTORS WITH SERVICE FACTORS	14-12
14.37.1	General	14-12
14.37.2	Temperature Rise—Medium Alternating-Current Motors	14-12
14.37.3	Temperature Rise—Small Alternating-Current Motors.....	14-12
14.38	CHARACTERISTICS OF PART-WINDING-START POLYPHASE INDUCTION MOTORS	14-12
14.39	COUPLING END-PLAY AND ROTOR FLOAT FOR HORIZONTAL ALTERNATING-CURRENT MOTORS	14-12
14.39.1	Preferred Hp Ratings for Motors with Ball Bearings	14-12
14.39.2	Limits for Motors with Sleeze Bearings	14-13
14.39.3	Drawing and Shaft Markings.....	14-13
14.40	OUTPUT SPEEDS FOR MEDIUM GEAR MOTORS OF PARALLEL CONSTRUCTION	14-14
14.41	APPLICATION OF MEDIUM ALTERNATING-CURRENT SQUIRREL- CAGE MACHINES WITH SEALED WINDINGS.....	14-14
14.41.1	Usual Service Conditions.....	14-14
14.41.2	Unusual Service Conditions.....	14-14
14.41.3	Hazardous Locations	14-15
14.42	APPLICATION OF V-BELT SHEAVES TO ALTERNATING CURRENT MOTORS HAVING ANTIFRICTION BEARINGS	14-15
14.42.1	Dimensions	14-15

14.42.2	Radial Overhung Load Limitations	14-15
14.43	ASEISMATIC CAPABILITY	14-15
14.44	POWER FACTOR OF THREE-PHASE, SQUIRREL-CAGE, MEDIUM MOTORS WITH CONTINUOUS RATINGS	14-17
14.44.1	Determination of Power Factor from Nameplate Data	14-17
14.44.2	Determination of Capacitor Rating for Connecting Power Factor to Desired Value	14-18
14.44.3	Determination of Corrected Power Factor for Specified Capacitor Rating	14-18
14.44.4	Application of Power Factor Correction Capacitors on Power Systems.....	14-18
14.44.5	Application of Power Factor Correction Capacitors on Motors Operated from Electronic Power Supply	14-18
14.45	BUS TRANSFER OR RECLOSING	14-19
14.46	ROTOR INERTIA FOR DYNAMIC BREAKING.....	14-19
14.47	EFFECTS OF LOAD ON MOTOR EFFICIENCY	14-19
14.48	REED FREQUENCY OF VERTICAL MACHINES	14-19

Section II SMALL (FRACTIONAL) AND MEDIUM (INTEGRAL) MACHINES

Part 14—APPLICATION DATA—DC SMALL AND MEDIUM MOTORS

14.0	SCOPE	14-21
14.60	OPERATION OF SMALL MOTORS ON RECTIFIED ALTERNATING CURRENT	14-21
14.60.1	General	14-21
14.60.2	Form Factor	14-21
14.61	OPERATION OF DIRECT-CURRENT MEDIUM MOTORS ON RECTIFIED ALTERNATING CURRENT	14-22
14.62	ARMATURE CURRENT RIPPLE	14-23
14.63	OPERATION ON A VARIABLE-VOLTAGE POWER SUPPLY	14-23
14.64	SHUNT FIELD HEATING AT STANDSTILL.....	14-24
14.65	BEARING CURRENTS.....	14-24
14.66	EFFECTS OF 50-HERTZ ALTERNATING-CURRENT POWER FREQUENCY	14-24
14.67	APPLICATION OF OVERHUNG LOADS TO MOTOR SHAFTS	14-25
14.67.1	Limitations.....	14-25
14.67.2	V-Belt Drives	14-26
14.67.3	Applications Other Than V-Belts.....	14-27
14.67.4	General	14-27
14.68	RATE OF CHANGE OF ARMATURE CURRENT	14-28

Section II SMALL (FRACTIONAL) AND MEDIUM (INTEGRAL) MACHINES

Part 15—DC Generators

15.0	SCOPE	15-1
15.10	KILOWATT, SPEED, AND VOLTAGE RATINGS	15-1
15.10.1	Standard Ratings	15-1
15.10.2	Exciters	15-2
15.11	NAMEPLATE TIME RATING, MAXIMUM AMBIENT TEMPERATURE, AND INSULATION SYSTEM CLASS	15-2
15.12	NAMEPLATE MARKING	15-2
TESTS AND PERFORMANCE		15-2
15.40	TEST PERFORMANCE.....	15-2
15.41	TEMPERATURE RISE	15-2
15.41.1	Temperature Rise for Maximum Ambient of 40°C.....	15-2
15.41.2	Temperature Rise for Ambients Higher than 40°C	15-3
15.41.3	Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C.....	15-3
15.42	SUCCESSFUL COMMUTATION	15-4

15.43	OVERLOAD	15-4
15.44	VOLTAGE VARIATION DUE TO HEATING.....	15-4
15.45	FLAT COMPOUNDING	15-4
15.46	TEST FOR REGULATION.....	15-4
15.47	OVERSPEEDS FOR GENERATORS	15-5
15.48	HIGH-POTENTIAL TEST.....	15-5
	15.48.1 Safety Precautions for Test Procedure.....	15-5
	15.48.2 Test Voltage.....	15-5
15.49	ROUTINE TESTS	15-5
15.50	FIELD DATA FOR DIRECT-CURRENT GENERATORS.....	15-5
15.51	REPORT OF TEST FORM	15-6
15.52	EFFICIENCY.....	15-6
	MANUFACTURING	15-7
15.60	DIRECTION OF ROTATION	15-7
15.61	EQUALIZER LEADS OF DIRECT-CURRENT GENERATORS.....	15-7

Section II SMALL (FRACTIONAL) AND MEDIUM (INTEGRAL) MACHINES

Part 18—DEFINITE PURPOSE MACHINES

18.1	SCOPE	18-1
	MOTORS FOR HERMETIC REFRIGERATION COMPRESSORS	18-1
18.2	CLASSIFIED ACCORDING TO ELECTRICAL TYPE	18-2
	RATINGS	18-3
18.3	VOLTAGE RATINGS	18-3
	18.3.1 Single-Phase Motors	18-3
	18.3.2 Polyphase Induction Motors	18-3
18.4	FREQUENCIES.....	18-3
18.5	SPEED RATINGS.....	18-3
	TESTS AND PERFORMANCE	18-3
18.6	OPERATING TEMPERATURE	18-3
18.7	BREAKDOWN TORQUE AND LOCKED-ROTOR CURRENT OF 60-HERTZ HERMETIC MOTORS	18-3
	18.7.1 Breakdown Torque	18-3
	18.7.2 Locked-Rotor Current	18-3
18.8	HIGH-POTENTIAL TEST.....	18-5
18.9	VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	18-5
18.10	DIRECTION OF ROTATION	18-5
18.11	TERMINAL LEAD MARKINGS	18-5
18.12	METHOD TEST FOR CLEANLINESS OF SINGLE-PHASE HERMETIC MOTORS HAVING STATOR DIAMETERS OF 6.292 INCHES AND SMALLER	18-5
	18.12.1 Stators.....	18-6
	18.12.2 Rotors	18-6
18.13	METHOD OF TEST FOR CLEANLINESS OF HERMETIC MOTORS HAVING STATOR DIAMETERS OF 8.777 INCHES AND SMALLER	18-6
	18.13.1 Purpose.....	18-6
	18.13.2 Description	18-6
	18.13.3 Sample Storage	18-6
	18.13.4 Equipment.....	18-6
	18.13.5 Procedure	18-7
	MANUFACTURING	18-7
18.14	ROTOR BORE DIAMETERS AND KEYWAY DIMENSIONS FOR 60-HERTZ HERMETIC MOTORS	18-8
18.15	DIMENSIONS FOR 60-HERTZ HERMETIC MOTORS	18-9
18.16	FORMING OF END WIRE.....	18-9
18.17	THERMAL PROTECTORS ASSEMBLED ON OR IN END	

WINDINGS OF HERMETIC MOTORS.....	18-9
18.18 LETTERING OF DIMENSIONS FOR HERMETIC MOTORS FOR HERMETIC COMPRESSORS	18-10
SMALL MOTORS FOR SHAFT-MOUNTED FANS AND BLOWERS	18-12
18.19 CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	18-12
RATINGS	18-12
18.20 VOLTAGE RATINGS	18-12
18.20.1 Single-Phase Motors	18-12
18.20.2 Polyphase Induction Motors	18-12
18.21 FREQUENCIES.....	18-12
18.22 HORSEPOWER AND SPEED RATINGS.....	18-12
18.22.1 Single-Speed Motors	18-12
18.22.2 Two-Speed Motors	18-12
TESTS AND PERFORMANCE	18-13
18.23 TEMPERATURE RISE	18-13
18.24 BASIS OF HORSEPOWER RATING	18-13
18.25 MAXIMUM LOCKED-ROTOR CURRENT—SINGLE-PHASE	18-13
18.26 HIGH-POTENTIAL TESTS.....	18-13
18.27 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	18-13
18.28 DIRECTION OF ROTATION	18-13
MANUFACTURING	18-13
18.29 GENERAL MECHANICAL FEATURES.....	18-13
18.30 DIMENSIONS AND LETTERING OF DIMENSIONS FOR MOTORS FOR SHAFT-MOUNTED FANS AND BLOWERS.....	18-13
18.31 TERMINAL MARKINGS.....	18-13
18.32 TERMINAL LEAD LENGTHS	18-14
SMALL MOTORS FOR BELTED FANS AND BLOWERS BUILT IN FRAMES 56 AND SMALLER	18-16
18.33 CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	18-16
RATINGS	18-16
18.34 VOLTAGE RATINGS	18-16
18.34.1 Single-Phase Motors	18-16
18.34.2 Polyphase Motors	18-16
18.35 FREQUENCIES.....	18-16
18.36 HORSEPOWER AND SPEED RATINGS.....	18-16
18.36.1 Single-Speed Motors	18-16
18.36.2 Two-Speed Motors	18-16
TESTS AND PERFORMANCE	18-17
18.37 TEMPERATURE RISE	18-17
18.38 BASIS OF HORSEPOWER RATING	18-17
18.39 MAXIMUM LOCKED-ROTOR CURRENT.....	18-17
18.40 HIGH-POTENTIAL TEST.....	18-17
18.41 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	18-17
18.42 DIRECTION OF ROTATION	18-17
MANUFACTURING	18-17
18.43 GENERAL MECHANICAL FEATURES.....	18-17
18.44 LETTERING OF DIMENSIONS FOR MOTORS FOR BELTED FANS AND BLOWERS	18-18
SMALL MOTORS FOR AIR CONDITIONING CONDENSERS AND EVAPORATOR FANS	18-19
18.45 CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	18-19
RATINGS	18-19
18.46 VOLTAGE RATINGS	18-19
18.47 FREQUENCIES.....	18-19
18.48 HORSEPOWER AND SPEED RATINGS.....	18-19
18.48.1 Horsepower Ratings	18-19

18.48.2	Speed Ratings	18-19
TESTS AND PERFORMANCE	18-19
18.49	TEMPERATURE RISE	18-19
18.50	BASIS OF HORSEPOWER RATINGS.....	18-19
18.51	HIGH-POTENTIAL TESTS	18-20
18.52	VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	18-20
18.53	VARIATION FROM RATED SPEED	18-20
18.54	TERMINAL MARKINGS—MULTISPEED SHADED-POLE MOTORS.....	18-20
MANUFACTURING	18-20
18.55	TERMINAL MARKINGS.....	18-20
18.56	TERMINAL LEAD LENGTHS	18-21
18.57	GENERAL MECHANICAL FEATURES.....	18-21
18.58	TERMINAL MARKINGS FOR NON-POLE-CHANGING MULTISPEED SINGLE-VOLTAGE NONREVERSIBLE PERMANENT-SPLIT CAPACITOR MOTORS AND SHADED POLE MOTORS.....	18-22
18.59	DIMENSIONS OF SHADED-POLE AND PERMANENT-SPLIT CAPACITOR MOTORS HAVING A P DIMENSION 4.38 INCHES AND LARGER	18-24
18.60	DIMENSIONS OF SHADED-POLE AND PERMANENT SPLIT CAPACITOR MOTORS HAVING A P DIMENSION SMALLER THAN 4.38 INCHES	18-25
18.61	DIMENSIONS FOR LUG MOUNTING FOR SHADED-POLE AND PERMANENT-SPLIT CAPACITOR MOTORS	18-25
APPLICATION DATA	18-26
18.62	NAMEPLATE CURRENT.....	18-26
RATINGS	18-26
18.63	EFFECT OF VARIATION FROM RATED VOLTAGE UPON OPERATING SPEED.....	18-26
18.64	INSULATION TESTING	18-26
	18.64.1 Test Conditions	18-26
	18.64.2 Test Method	18-27
18.65	SERVICE CONDITIONS.....	18-27
SMALL MOTORS AND SUMP PUMPS	18-30
18.66	CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	18-30
RATINGS	18-30
18.67	VOLTAGE RATINGS	18-30
18.68	FREQUENCIES	18-30
18.69	HORSEPOWER AND SPEED RATINGS.....	18-30
	18.69.1 Horsepower Ratings	18-30
	18.69.2 Speed Ratings	18-30
TESTS AND PERFORMANCE	18-30
18.70	TEMPERATURE RISE	18-30
18.71	BASIS OF HORSEPOWER RATINGS.....	18-30
18.72	TORQUE CHARACTERISTICS	18-30
18.73	HIGH-POTENTIAL TESTS	18-31
18.74	VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	18-31
18.75	DIRECTION OF ROTATION	18-31
MANUFACTURING	18-31
18.76	GENERAL MECHANICAL FEATURES.....	18-31
18.77	DIMENSIONS FOR SUMP PUMP MOTORS, TYPE K.....	18-31
18.78	FRAME NUMBER AND FRAME SUFFIX LETTER.....	18-31
SMALL MOTORS FOR GASOLINE DISPENSING PUMPS	18-33
18.79	CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	18-33
RATINGS	18-33
18.80	VOLTAGE RATINGS	18-33

18.80.1 Single-Phase Motors	18-33
18.30.2 Polyphase Induction Motors	18-33
18.81 FREQUENCIES	18-33
18.82 HORSEPOWER AND SPEED RATINGS.....	18-32
18.82.1 Horsepower Ratings	18-32
18.82.2 Speed Ratings	18-33
TESTS AND PERFORMANCE	18-33
18.83 TEMPERATURE RISE	18-33
18.84 BASIS OF HORSEPOWER RATINGS.....	18-34
18.85 LOCKED-ROTOR TORQUE	18-34
18.86 LOCKED-ROTOR CURRENT	18-34
18.87 HIGH-POTENTIAL TEST.....	18-35
18.88 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	18-35
18.89 DIRECTION OF ROTATION	18-35
MANUFACTURING	18-35
18.90 GENERAL MECHANICAL FEATURES.....	18-35
18.91 FRAME NUMBER AND FRAME SUFFIX LETTER.....	18-35
18.92 DIMENSIONS FOR GASOLINE DISPENSING PUMP MOTORS, TYPE G.....	18-36
SMALL MOTORS FOR OIL BURNERS	18-37
18.93 CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	18-37
RATINGS	18-37
18.94 VOLTAGE RATINGS	18-37
18.95 FREQUENCIES	18-37
18.96 HORSEPOWER AND SPEED RATINGS.....	18-37
18.96.1 Horsepower Ratings	18-37
18.96.2 Speed Ratings	18-37
TESTS AND PERFORMANCE	18-37
18.97 TEMPERATURE RISE	18-37
18.98 BASIS OF HORSEPOWER RATING	18-38
18.99 LOCKED-ROTOR CHARACTERISTICS.....	18-38
18.100 HIGH-POTENTIAL TEST.....	18-38
18.101 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	18-38
18.102 DIRECTION OF ROTATION	18-38
MANUFACTURING	18-38
18.103 GENERAL MECHANICAL FEATURES.....	18-38
18.104 DIMENSIONS FOR FACE-MOUNTING MOTORS FOR OIL- BURNERS, TYPES M AND N	18-39
18.104.1 Dimensions	18-39
18.105 TOLERANCES.....	18-39
18.106 FRAME NUMBER AND FRAME SUFFIX LETTER.....	18-39
18.106.1 Suffix Letter M.....	18-39
18.106.2 Suffix Letter N	18-40
SMALL MOTORS FOR HOME LAUNDRY EQUIPMENT	18-41
18.107 CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	18-41
RATINGS	18-41
18.108 VOLTAGE RATINGS	18-41
18.109 FREQUENCIES	18-41
18.110 HORSEPOWER AND SPEED RATINGS.....	18-41
18.110.1 Horsepower Ratings	18-41
18.110.2 Speed Ratings	18-41
18.111 NAMEPLATE MARKING	18-41
TESTS AND PERFORMANCE	18-42
18.112 TEMPERATURE RISE	18-42
18.113 BASIS OF HORSEPOWER RATING	18-42

18.114	MAXIMUM LOCKED-ROTOR CURRENT	18-42
18.115	HIGH-POTENTIAL TEST.....	18-42
18.116	VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	18-42
	MANUFACTURING	18-42
18.117	GENERAL MECHANICAL FEATURES	18-42
18.118	DIMENSIONS FOR MOTORS FOR HOME LAUNDRY EQUIPMENT	18-43
	MOTORS AND JET PUMPS	18-44
18.119	CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	18-44
	RATINGS	18-44
18.120	VOLTAGE RATINGS	18-44
	18.120.1 Single-Phase Motors	18-44
	18.120.2 Polyphase Induction Motors	18-44
18.121	FREQUENCIES	18-44
18.122	HORSEPOWER, SPEED, AND SERVICE FACTOR RATINGS.....	18-44
	TEST AND PERFORMANCE	18-45
18.123	TEMPERATURE RISE	18-45
18.124	BASIS OF HORSEPOWER RATING	18-45
18.125	TORQUE CHARACTERISTICS	18-45
18.126	MAXIMUM LOCKED-ROTOR CURRENT.....	18-45
18.127	HIGH-POTENTIAL TEST.....	18-45
18.128	VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	18-45
18.129	DIRECTION OF ROTATION	18-45
	MANUFACTURING	18-45
18.130	GENERAL MECHANICAL FEATURES.....	18-45
18.131	DIMENSION FOR FACE-MOUNTED MOTORS FOR JET PUMPS.....	18-46
18.132	FRAME NUMBER AND FRAME SUFFIX LETTER.....	18-47
	SMALL MOTORS FOR COOLANT PUMPS	18-48
18.133	CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	18-48
	RATINGS	18-48
18.134	VOLTAGE RATINGS	18-48
	18.134.1 Single-Phase Motors	18-48
	18.134.2 Polyphase Induction Motors	18-48
	18.134.3 Direct-current Motors	18-48
18.135	FREQUENCIES	18-48
18.136	HORSEPOWER AND SPEED RATINGS.....	18-49
	TESTS AND PERFORMANCE	18-50
18.137	TEMPERATURE RISE	18-50
18.138	BASIS OF HORSEPOWER RATING	18-50
18.139	TORQUE CHARACTERISTICS	18-50
18.140	MAXIMUM LOCKED-ROTOR CURRENT.....	18-50
18.141	HIGH-POTENTIAL TEST.....	18-50
18.142	VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	18-50
18.143	DIRECTION OF ROTATION	18-50
	MANUFACTURING	18-51
18.144	GENERAL MECHANICAL FEATURES.....	18-51
	SUBMERSIBLE MOTORS FOR DEEP WELL PUMPS—4-INCH	18-52
18.145	CLASSIFICATION TO ELECTRICAL TYPE.....	18-52
	RATINGS	18-52
18.146	VOLTAGE RATINGS	18-52
	18.146.1 Single-Phase Motors	18-52
	18.146.2 Polyphase Induction Motors	18-52
18.147	FREQUENCIES	18-52
18.148	HORSEPOWER AND SPEED RATINGS.....	18-52
	18.148.1 Horsepower Ratings	18-52
	18.148.2 Speed Ratings	18-52
	TESTS AND PERFORMANCE	18-53

18.149	BASIS OF HORSEPOWER RATING	18-53
18.150	LOCKED-ROTOR CURRENT	18-53
18.150.1	Single-Phase Small Motors	18-53
18.150.2	Single-Phase Medium Motors.....	18-53
18.152.3	Three-Phase Medium Motors	18-53
18.151	HIGH-POTENTIAL TEST.....	18-53
18.152	VARIATION FROM RATED VOLTAGE AT CONTROL BOX.....	18-53
18.153	VARIATION FROM RATED FREQUENCY	18-53
18.154	DIRECTION OF ROTATION	18-53
18.155	THRUST CAPACITY	18-53
	MANUFACTURING	18-53
18.156	TERMINAL LEAD MARKINGS	18-53
18.157	GENERAL MECHANICAL FEATURES.....	18-54
	SUBMERSIBLE MOTORS FOR DEEP WELL PUMPS—6-INCH	18-55
18.158	CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	18-55
	RATINGS	18-55
18.159	VOLTAGE RATINGS	18-55
18.159.1	Single-Phase Motors	18-55
18.159.2	Polyphase Induction Motors	18-55
18.160	FREQUENCIES.....	18-55
18.161	HORSEPOWER AND SPEED RATINGS.....	18-55
18.161.1	Horsepower Ratings	18-55
	TESTS AND PERFORMANCE	18-55
18.162	BASIS FOR HORSEPOWER RATING.....	18-55
18.163	LOCKED-ROTOR CURRENT	18-55
18.164	HIGH-POTENTIAL TESTS	18-56
18.165	VARIATION FROM RATED VOLTAGE AT CONTROL BOX.....	18-56
18.166	VARIATION FROM RATED FREQUENCY	18-56
18.167	DIRECTION OF ROTATION	18-56
18.168	THRUST CAPACITY	18-56
	MANUFACTURING	18-56
18.169	TERMINAL LEAD MARKINGS	18-56
18.170	GENERAL-MECHANICAL FEATURES.....	18-57
	SUBMERSIBLE MOTORS FOR DEEP WELL PUMPS—8-INCH	18-58
18.171	CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	18-58
	RATINGS	18-58
18.172	VOLTAGE RATINGS	18-58
18.173	FREQUENCIES.....	18-58
18.174	HORSEPOWER AND SPEED RATINGS.....	18-58
18.174.1	Horsepower Ratings	18-58
18.174.2	Speed Ratings	18-58
	TESTS AND PERFORMANCE	18-58
18.175	LOCKED-ROTOR CURRENT	18-58
18.176	HIGH-POTENTIAL TEST.....	18-58
18.177	VARIATION FROM RATED VOLTAGE AT CONTROL BOX.....	18-59
18.178	VARIATION FROM RATED FREQUENCY	18-59
18.179	DIRECTION OF ROTATION	18-59
18.180	THRUST CAPACITY	18-59
18.181	GENERAL MECHANICAL FEATURES.....	18-60
	MEDIUM DC ELEVATOR MOTORS	18-61
18.182	CLASSIFICATION ACCORDING TO TYPE.....	18-61
18.182.1	Class DH.....	18-61
18.182.2	Class DL	18-61
	RATINGS	18-61
18.183	VOLTAGE RATINGS	18-61
18.184	HORSEPOWER AND SPEED RATINGS.....	18-61

18.184.1 Class DH.....	18-61
18.184.2 Class DL.....	18-61
18.185 BASIS OF RATING.....	18-62
18.185.1 Class DH.....	18-62
18.185.2 Class DL.....	18-62
18.186 NAMEPLATE MARKINGS.....	18-62
TESTS AND PERFORMANCE	18-62
18.187 ACCELERATION AND DECELERATION CAPACITY.....	18-62
18.188 VARIATION IN SPEED DUE TO LOAD.....	18-62
18.188.1 Class DH.....	18-62
18.188.2 Class DL.....	18-62
18.189 VARIATION FROM RATED SPEED.....	18-62
18.190 VARIATION IN SPEED DUE TO HEATING.....	18-62
18.190.1 Open-Loop Control System.....	18-62
18.190.2 Closed-Loop Control System.....	18-63
18.191 HIGH-POTENTIAL TEST.....	18-63
18.192 TEMPERATURE RISE.....	18-63
MOTOR-GENERATOR SETS FOR DC ELEVATOR MOTORS	18-64
RATINGS	18-64
18.193 BASIS OF RATING.....	18-64
18.193.1 Time Rating.....	18-64
18.193.2 Relation to Elevator Motor.....	18-64
18.194 GENERATOR VOLTAGE RATINGS.....	18-64
18.194.1 Value.....	18-64
18.194.2 Maximum Value.....	18-64
TESTS AND PERFORMANCE	18-64
18.195 VARIATION IN VOLTAGE DUE TO HEATING.....	18-64
18.195.1 Open-Loop Control System.....	18-64
18.195.2 Closed-Loop Control System.....	18-64
18.196 OVERLOAD.....	18-64
18.197 HIGH-POTENTIAL TEST.....	18-65
18.198 VARIATION FROM RATED VOLTAGE.....	18-65
18.199 VARIATION FROM RATED FREQUENCY.....	18-65
18.200 COMBINED VARIATION OF VOLTAGE AND FREQUENCY.....	18-65
18.201 TEMPERATURE RISE.....	18-65
18.201.1 Induction Motors.....	18-65
18.201.2 Direct-Current Adjustable-Voltage Generators.....	18-65
MEDIUM AC POLYPHASE ELEVATOR MOTORS	18-66
18.202 CLASSIFICATION ACCORDING TO ELECTRICAL TYPE.....	18-66
18.202.1 AH1.....	18-65
18.202.2 AH2.....	18-66
18.202.3 AH3.....	18-66
RATINGS	18-66
18.203 BASIS OF RATING—ELEVATOR MOTORS.....	18-66
18.204 VOLTAGE RATINGS.....	18-66
18.205 FREQUENCY.....	18-66
18.206 HORSEPOWER AND SPEED RATINGS.....	18-67
TESTS AND PERFORMANCE	18-67
18.207 LOCKED-ROTOR TORQUE FOR SINGLE-SPEED SQUIRREL- CAGE ELEVATOR MOTORS.....	18-67
18.208 TIME-TEMPERATURE RATING.....	18-67
18.209 HIGH-POTENTIAL TEST.....	18-67
18.210 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY.....	18-67
MANUFACTURING	18-68
18.211 NAMEPLATE MARKING.....	18-68
MEDIUM AC CRANE MOTORS	18-69

RATINGS..... 18-69

18.212 VOLTAGE RATINGS 18-69

18.213 FREQUENCIES 18-69

18.214 HORSEPOWER AND SPEED RATINGS..... 18-69

18.215 SECONDARY DATA FOR WOUND-ROTOR CRANE MOTORS..... 18-70

18.216 NAMEPLATE MARKING 18-70

18.217 FRAME SIZES FOR TWO- AND THREE-PHASE 60-HERTZ
OPEN AND TOTALLY ENCLOSED WOUND-ROTOR CRANE
MOTORS HAVING CLASS B INSULATION SYSTEMS 18-71

TESTS AND PERFORMANCE 18-71

18.218 TIME RATINGS 18-71

18.219 TEMPERATURE RISE 18-71

18.220 BREAKDOWN TORQUE 18-71

 18.220.1 Minimum Value 18-71

 18.221.2 Maximum Value 18-71

18.222 HIGH-POTENTIAL TEST..... 18-71

18.223 OVERSPEEDS 18-72

18.224 PLUGGING 18-72

18.225 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY 18-72

18.226 ROUTINE TESTS 18-72

18.227 BALANCE OF MOTORS 18-72

18.228 BEARINGS 18-72

18.229 DIMENSIONS FOR ALTERNATING-CURRENT WOUND-ROTOR
OPEN AND TOTALLY ENCLOSED CRANE MOTORS..... 18-73

18.230 DIMENSIONS AND TOLERANCES FOR ALTERNATING-
CURRENT OPEN AND TOTALLY ENCLOSED WOUND-ROTOR
CRANE MOTORS HAVING ANTIFRICTION BEARINGS..... 18-74

**MEDIUM SHELL-TYPE MOTORS FOR WOODWORKING AND
MACHINE-TOOL APPLICATIONS** 18-76

18.231 DEFINITION OF SHELL-TYPE MOTOR 18-76

18.232 TEMPERATURE RISE—SHELL-TYPE MOTOR 18-76

18.233 TEMPERATURE RISE FOR 60-HERTZ SHELL-TYPE MOTORS
OPERATED ON 50-HERTZ 18-76

18.234 OPERATION AT OTHER FREQUENCIES—SHELL-TYPE MOTORS..... 18-76

18.235 RATINGS AND DIMENSIONS FOR SHELL-TYPE MOTORS..... 18-76

 18.235.1 Rotor Bore and Keyway Dimensions, Three-Phase
 60-Hertz 40°C Open Motors, 208, 220, 440, and 550 Volts 18-76

 18.235.2 BH and BJ Dimensions in Inches, Open Type Three-Phase
 60-Hertz 40°C Continuous, 208, 220, 440, and 550 Volts..... 18-77

18.236 LETTERING FOR DIMENSION SHEETS FOR SHELL-TYPE MOTORS 18-78

**MEDIUM AC SQUIRREL-CAGE INDUCTION MOTORS FOR
VERTICAL TURBINE PUMP APPLICATIONS**..... 18-78

18.237 DIMENSION FOR TYPE VP VERTICAL SOLID-SHAFT, SINGLE-PHASE
AND POLYPHASE, DIRECT CONNECTED SQUIRREL-CAGE
INDUCTION MOTORS FOR VERTICAL TURBINE PUMP
APPLICATIONS..... 18-79

18.238 DIMENSIONS FOR TYPE P AND PH ALTERNATING-CURRENT
SQUIRREL-CAGE VERTICAL HOLLOW-SHAFT MOTORS FOR
VERTICAL TURBINE PUMP APPLICATIONS..... 18-81

 18.238.1 Base Dimensions 18-81

 18.238.2 Coupling Dimensions 18-82

**MEDIUM AC SQUIRREL-CAGE INDUCTION MOTORS FOR
CLOSE-COUPLED PUMPS** 18-83

RATINGS 18-83

18.239 VOLTAGE RATINGS 18-83

18.240 FREQUENCIES 18-83

18.241	NAMEPLATE MARKINGS	18-83
18.242	NAMEPLATE RATINGS	18-83
	TESTS AND PERFORMANCE	18-83
18.243	TEMPERATURE RISE	18-83
18.244	TORQUES	18-83
18.245	LOCKED-ROTOR CURRENTS	18-83
18.246	HIGH-POTENTIAL TEST.....	18-83
18.247	VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	18-83
18.248	BALANCE OF MOTORS	18-83
	MANUFACTURING	18-83
18.249	FRAME ASSIGNMENTS	18-83
18.250	DIMENSIONS FOR TYPE JM AND JP ALTERNATING-CURRENT FACE-MOUNTING CLOSE-COUPLED PUMP MOTORS HAVING ANTIFRICTION BEARINGS	18-84
18.251	DIMENSIONS FOR TYPE LP AND LPH VERTICAL SOLID-SHAFT SINGLE-PHASE AND POLYPHASE DIRECT-CONNECTED SQUIRREL- CAGE INDUCTION MOTORS (HAVING THE THRUST BEARING IN THE MOTOR) FOR CHEMICAL PROCESS IN-LINE PUMP APPLICATIONS.....	18-89
18.252	DIMENSIONS FOR TYPE HP AND HPH VERTICAL SOLID-SHAFT SINGLE-PHASE AND POLYPHASE DIRECT-CONNECTED SQUIRREL-CAGE INDUCTION MOTORS FOR PROCESS AND IN-LINE PUMP APPLICATIONS	18-91
	DC PERMANENT-MAGNET TACHOMETER GENERATORS FOR CONTROL SYSTEMS	18-93
18.253	CLASSIFICATION ACCORDING TO ELECTRICAL TYPE	18-93
18.254	CLASSIFICATION ACCORDING TO OUTPUT VOLTAGE RATING.....	18-93
	RATINGS	18-93
18.255	OUTPUT VOLTAGE RATINGS	18-93
18.256	CURRENT RATING.....	18-93
18.257	SPEED RATINGS.....	18-93
	TESTS AND PERFORMANCE	18-93
18.258	TEST METHODS.....	18-93
18.259	TEMPERATURE RISE	18-93
18.260	VARIATION FROM RATED OUTPUT VOLTAGE.....	18-94
	18.260.1 High-Voltage Type	18-94
	18.260.2 Low-Voltage Type.....	18-94
18.261	HIGH-POTENTIAL TESTS	18-94
	18.261.1 Test	18-94
	18.261.2 Application	18-94
18.262	OVERSPEED.....	18-94
18.263	PERFORMANCE CHARACTERISTICS.....	18-94
	18.263.1 High-Voltage Type	18-94
	18.263.2 Low-Voltage Type	18-95
	MANUFACTURING	18-95
18.264	NAMEPLATE MARKING	18-95
	18.264.1 High-Voltage Type	18-95
	18.264.2 Low-Voltage Type.....	18-95
18.265	DIRECTION OF ROTATION	18-95
18.266	GENERAL MECHANICAL FEATURES.....	18-95
	18.266.1 High-Voltage Type	18-96
	18.266.2 Low-Voltage Type.....	18-96
18.267	TERMINAL MARKINGS.....	18-96
	TORQUE MOTORS	18-97
18.268	DEFINITION.....	18-97
18.269	NAMEPLATE MARKINGS	18-97
	18.269.1 AC Torque Motors	18-97
	18.269.2 DC Torque Motors	18-97

SMALL MOTORS FOR CARBONATOR PUMPS 18-98

18.270 CLASSIFICATION ACCORDING TO ELECTRICAL TYPE 18-98

RATINGS 18-98

18.271 VOLTAGE RATINGS 18-98

18.272 FREQUENCIES 18-98

18.273 HORSEPOWER AND SPEED RATING 18-98

 18.273.1 Horsepower Ratings 18-98

 18.273.2 Speed Ratings 18-98

TESTS AND PERFORMANCE 18-98

18.274 TEMPERATURE RISE 18-98

18.275 BASIS OF HORSEPOWER RATING 18-98

18.276 HIGH-POTENTIAL TEST 18-98

18.277 MAXIMUM LOCKED-ROTOR CURRENT—SINGLE PHASE 18-98

18.278 VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY 18-98

18.279 DIRECTION OF ROTATION 18-98

MANUFACTURING 18-99

18.280 GENERAL MECHANICAL FEATURE 18-99

18.281 DIMENSIONS FOR CARBONATOR PUMP MOTORS 18-99

Section III LARGE MACHINES

Part 20—LARGE MACHINES—INDUCTION MACHINES

20.1 SCOPE 20-1

20.2 BASIS OF RATING 20-1

20.3 MACHINE POWER AND SPEED RATINGS 20-1

20.4 POWER RATINGS OF MULTISPEED MACHINES 20-2

 20.4.1 Constant Power 20-2

 20.4.2 Constant Torque 20-2

 20.4.3 Variable Torque 20-2

20.5 VOLTAGE RATINGS 20-3

20.6 FREQUENCIES 20-3

20.7 SERVICE FACTOR 20-3

 20.7.1 Service Factor of 1.0 20-3

 20.7.2 Service Factor of 1.15 20-3

 20.7.3 Application of Motors with a Service Factor of 1.15 20-3

TESTS AND PERFORMANCE 20-4

20.8 TEMPERATURE RISE 20-4

 20.8.1 Machines with a 1.0 Service Factor at Rated Load 20-4

 20.8.2 Machines with a 1.15 Service Factor at Service Factor Load 20-5

 20.8.3 Temperature Rise for Ambients Higher than 40°C 20-5

 20.8.4 Temperature Rise for Altitudes Greater than 3300 Feet
 (1000 Meters) 20-5

 20.8.5 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40°C,
 but Not Below 0°C 20-5

20.9 CODE LETTERS (FOR LOCKED-ROTOR KVA) 20-6

20.10 TORQUE 20-7

 20.10.1 Standard Torque 20-7

 20.10.2 High Torque 20-8

 20.10.3 Motor Torques When Customer Specifies A Custom Load Curve 20-8

 20.10.4 Motor With 4.5 pu and Lower Locked-Rotor Current 20-8

20.11 LOAD WK² FOR POLYPHASE SQUIRREL-CASE INDUCTION
MOTORS 20-8

20.12 NUMBER OF STARTS 20-9

 20.12.1 Starting Capability 20-9

 20.12.2 Additional Starts 20-9

 20.12.3 Information Plate 20-9

20.13 OVERSPEEDS 20-9

20.14	VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	20-11
	20.14.1 Running.....	20-11
	20.14.2 Starting.....	20-11
20.15	OPERATION OF INDUCTION MACHINES FROM VARIABLE-FREQUENCY OR VARIABLE-VOLTAGE POWER SUPPLIES, OR BOTH.....	20-11
20.16	TESTS	20-12
	20.16.1 Test Methods	20-12
	20.16.2 Routine Tests on Machines Completely Assembled in Factory	20-12
	20.16.3 Routine Tests on Machines Not Completely Assembled in Factory.....	20-12
20.17	HIGH-POTENTIAL TESTS	20-12
	20.17.1 Safety Precautions and Test Procedure.....	20-12
	20.17.2 Test Voltage—Primary Windings	20-12
	20.17.3 Test Voltage—Secondary Windings of Wound Rotors.....	20-12
20.18	MACHINE WITH SEALED WINDINGS—CONFORMANCE TESTS	20-13
	20.18.1 Test for Stator Which Can be Submerged.....	20-13
	20.18.2 Test for Stator Which Cannot be Submerged.....	20-13
20.19	MACHINE SOUND	20-13
20.20	REPORT OF TEST FORM FOR INDUCTION MACHINES	20-14
20.21	EFFICIENCY	20-14
20.22	MECHANICAL VIBRATION.....	20-14
20.23	REED FREQUENCY OF VERTICAL MACHINES	20-15
20.24	EFFECTS OF UNBALANCED VOLTAGES ON THE PERFORMANCE OF POLYPHASE SQUIRREL-CAGE INDUCTION MOTORS	20-15
	20.24.1 Effect on Performance—General.....	20-16
	20.24.2 Voltage Unbalance Defined	20-16
	20.24.3 Torques.....	20-16
	20.24.4 Full-Load Speed	20-16
	20.24.5 Currents	20-16
	MANUFACTURING	20-16
20.25	NAMEPLATE MARKING	20-16
	20.25.1 Alternating-Current Polyphase Squirrel-Cage Motors	20-17
	20.25.2 Polyphase Wound-Rotor Motors.....	20-17
	20.25.3 Polyphase Squirrel-Cage Generators.....	20-17
	20.25.4 Polyphase Wound-Rotor Generators	20-18
20.26	MOTOR TERMINAL HOUSINGS AND BOXES	20-18
	20.26.1 Box Dimensions.....	20-18
	20.26.2 Accessory Lead Terminations	20-18
	20.26.3 Lead Terminations of Accessories Operating at 50 Volts or Less.....	20-18
20.27	EMBEDDED TEMPERATURE DETECTORS.....	20-19
	APPLICATION DATA	20-21
20.28	SERVICE CONDITIONS.....	20-21
	20.28.1 General	20-21
	20.28.2 Usual Service Conditions.....	20-21
	20.28.3 Unusual Service Conditions.....	20-21
20.29	END PLAY AND ROTOR FLOAT FOR COUPLED SLEEVE BEARING HORIZONTAL INDUCTION MACHINES.....	20-22
	20.29.1 General	20-22
	20.29.2 Limits.....	20-22
	20.29.3 Marking Requirements.....	20-22
20.30	PULSATING STATOR CURRENT IN INDUCTION MOTORS.....	20-23
20.31	ASEISMATIC CAPABILITY	20-23
	20.31.1 General	20-23
	20.31.2 Frequency Response Spectrum	20-23
	20.31.3 Units for Capability Requirements	20-23
	20.31.4 Recommended Peak Acceleration Limits.....	20-23

20.32	BELT, CHAIN, AND GEAR DRIVE	20-24
20.33	BUS TRANSFER OR RECLOSING	20-24
	20.33.1 Slow Transfer or Reclosing.....	20-24
	20.33.2 Fast Transfer or Reclosing	20-24
20.34	POWER FACTOR CORRECTION	20-25
20.35	SURGE CAPABILITIES OF AC WINDINGS WITH FORM- WOUND COILS	20-25
	20.35.1 General	20-25
	20.35.2 Surge Sources	20-25
	20.35.3 Factors Influencing Magnitude and Rise Time	20-25
	20.35.4 Surge Protection	20-26
	20.35.5 Surge Withstand Capability for Standard Machines	20-26
	20.35.6 Special Surge Withstand Capability	20-26
	20.35.7 Testing	20-26
	20.35.8 Test Voltage Values.....	20-26
20.36	MACHINES OPERATING ON AN UNGROUNDED SYSTEM	20-26
20.37	OCCASIONAL EXCESS CURRENT	20-27

Section III LARGE MACHINES

Part 21—LARGE MACHINES—SYNCHRONOUS MOTORS

	RATINGS	21-1
21.1	SCOPE	21-1
21.2	BASIS OF RATING	21-1
21.3	HORSEPOWER AND SPEED RATINGS.....	21-2
21.4	POWER FACTOR.....	21-2
21.5	VOLTAGE RATINGS	21-2
	21.5.1 Voltage Ratings.....	21-2
	21.5.2 Preferred Motor Output/Voltage Rating	21-3
21.6	FREQUENCIES	21-3
21.7	EXCITATION VOLTAGE	21-3
21.8	SERVICE FACTOR	21-3
	21.8.1 Service Factor of 1.0.....	21-3
	21.8.2 Service Factor of 1.15.....	21-3
	21.8.3 Application of Motor with 1.15 Service Factor	21-3
21.9	TYPICAL KW RATINGS OF EXCITERS FOR 60-HERTZ SYNCHRONOUS MOTORS.....	21-4
	TESTS AND PERFORMANCE	21-9
21.10	TEMPERATURE RISE—SYNCHRONOUS MOTORS	21-9
	21.10.1 Machines with 1.0 Service Factor at Rated Load	21-9
	21.10.2 Machines with 1.15 Service Factor at Service Factor Load	21-9
	21.10.3 Temperature Rise for Ambients Higher than 40°C	21-10
	21.10.4 Temperature Rise for Altitudes Greater than 3300 Feet (1000 Meters).....	21-10
	21.10.5 Temperature Rise for Air-Cooled Motors for Ambients Lower than 40°C, but Not Below 0°C.....	21-10
21.11	TORQUES	21-11
	21.11.1 General	21-11
	21.11.2 Motor Torques When Customer Supplies Load Curve.....	21-11
21.12	NORMAL WK ² OF LOAD.....	21-11
21.13	NUMBER OF STARTS	21-12
	21.13.1 Starting Capability.....	21-12
	21.13.2 Additional Starts.....	21-12
	21.13.3 Information Plate.....	21-12
21.14	EFFICIENCY	21-12
21.15	OVERSPEED.....	21-13
21.16	OPERATION AT OTHER THAN RATED POWER FACTORS	21-13
	21.16.1 Operation of an 0.8 Power-factor Motor at 1.0 Power-factor.....	21-13

21.16.2	Operation of a 1.0 Power-factor Motor at 0.8 Power-factor.....	21-14
21.17	VARIATIONS FROM RATED VOLTAGE AND RATED FREQUENCY	21-14
21.17.1	Running.....	21-14
21.17.2	Starting.....	21-14
21.18	OPERATION OF SYNCHRONOUS MOTORS FROM VARIABLE-FREQUENCY POWER SUPPLIES	21-14
21.19	SPECIFICATION FORM FOR SLIP-RING SYNCHRONOUS MOTORS	21-18
21.20	SPECIFICATION FORM FOR BRUSHLESS SYNCHRONOUS MOTORS.....	21-19
21.21	ROUTINE TESTS	21-20
21.21.1	Motors Not Completely Assembled in the Factory	21-20
21.21.2	Motors Completely Assembled in the Factory	21-20
21.22	HIGH-POTENTIAL TESTS	21-20
21.22.1	Safety Precautions and Test Procedure	21-20
21.22.2	Test Voltage—Armature Windings	21-20
21.22.3	Test Voltage—Field Windings, Motors with Slip Rings	21-20
21.22.4	Test Voltage—Assembled Brushless Motor Field Windings and Exciter Armature Winding	21-20
21.22.5	Test Voltage—Brushless Exciter Field Winding	21-21
21.23	MACHINE SOUND	21-21
21.24	MECHANICAL VIBRATION.....	21-21
	MANUFACTURING	21-21
21.25	NAMEPLATE MARKING	21-21
21.26	MOTOR TERMINAL HOUSINGS AND BOXES	21-22
21.26.1	Box Dimensions	21-22
21.26.2	Accessory Lead Terminations	21-22
21.26.3	Lead Terminations of Accessories Operating at 50 Volts or Less.....	21-22
21.27	EMBEDDED DETECTORS	21-24
	APPLICATION DATA	21-25
21.28	SERVICE CONDITIONS.....	21-25
21.28.1	General	21-25
21.28.2	Usual Service Conditions.....	21-25
21.28.3	Unusual Service Conditions.....	21-25
21.29	EFFECTS OF UNBALANCED VOLTAGES ON THE PERFORMANCE OF POLYPHASE SYNCHRONOUS MOTORS.....	21-26
21.29.1	Effect on Performance	21-27
21.29.2	Voltage Unbalanced Defined	21-27
21.30	COUPLING END PLAY AND ROTOR FLOAT FOR HORIZONTAL MOTORS	21-27
21.31	BELT, CHAIN, AND GEAR DRIVE.....	21-27
21.32	PULSATING ARMATURE CURRENT.....	21-27
21.33	TORQUE PULSATIONS DURING STARTING OF SYNCHRONOUS MOTORS	21-28
21.34	BUS TRANSFER OR RECLOSING	21-28
21.34.1	Slow Transfer of Reclosing.....	21-28
21.34.2	Fast Transfer of Reclosing.....	21-28
21.34.3	Bus Transfer Procedure.....	21-29
21.35	CALCULATION OF NATURAL FREQUENCY OF SYNCHRONOUS MACHINES DIRECT-CONNECTED TO RECIPROCATING MACHINERY	21-29
21.35.1	Undamped Natural Frequency.....	21-29
21.35.2	Synchronizing Torque Coefficient, P_r	21-29
21.35.3	Factors Influencing P_r	21-29
21.36	TYPICAL TORQUE REQUIREMENTS	21-29
21.37	COMPRESSOR FACTORS.....	21-34
21.38	SURGE CAPABILITIES OF AC WINDINGS WITH FORM-WOUND COILS	21-35
21.39	MACHINES OPERATING ON AN UNGROUNDED SYSTEM	21-35

21.40 OCCASIONAL EXCESS CURRENT21-35

Section III LARGE MACHINES

Part 23—LARGE MACHINES—DC MOTORS LARGER THAN 1.25 HORSEPOWER PER RPM, OPEN TYPE

CLASSIFICATION23-1

23.1 SCOPE23-1

23.2 GENERAL INDUSTRIAL MOTORS23-1

23.3 METAL ROLLING MILL MOTORS23-1

 23.3.1 Class N Metal Rolling Mill Motors23-1

 23.3.2 Class S Metal Rolling Mill Motors23-1

23.4 REVERSING HOT MILL MOTORS23-1

RATINGS23-2

23.5 BASIS OF RATING23-2

23.6 HORSEPOWER, SPEED, AND VOLTAGE RATINGS23-3

 23.6.1 General Industrial Motors and Metal Rolling Mill Motors, Classes N and S23-3

 23.6.2 Reversing Hot Mill Motors23-4

23.7 SPEED RATINGS BY FIELD CONTROL FOR 250-VOLT DIRECT-CURRENT MOTORS23-5

23.8 SPEED RATINGS BY FIELD CONTROL FOR 500- OR 700-VOLT DIRECT-CURRENT MOTORS23-6

TESTS AND PERFORMANCE23-8

23.9 TEMPERATURE RISE23-8

 23.9.1 Temperature Rise for Ambients Higher than 40°C23-9

 23.9.2 Temperature Rise for Altitudes Greater than 3300 Feet (1000 Meters)23-9

 23.9.3 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C23-9

23.10 OVERLOAD CAPABILITY23-10

 23.10.1 General Industrial Motors23-10

 23.10.2 Metal Rolling Mill Motors (Excluding Reversing Hot Mill Motors)—Open, Forced-Ventilated, and Totally Enclosed Water-Air-Cooled23-10

 23.10.3 Reversing Hot Mill Motors—Forced-Ventilated and Totally Enclosed Water-Air-Cooled23-11

23.11 MOMENTARY LOAD CAPACITY23-11

23.12 SUCCESSFUL COMMUTATION23-11

23.13 EFFICIENCY23-11

23.14 TYPICAL REVERSAL TIME OF REVERSING HOT MILL MOTORS23-12

23.15 IMPACT SPEED DROP OF A DIRECT-CURRENT MOTOR23-12

23.16 OVERSPEED23-12

23.17 VARIATION FROM RATED VOLTAGE23-13

 23.17.1 Steady State23-13

 23.17.2 Transient Voltages of Microsecond Duration23-13

23.18 FIELD DATA FOR DIRECT-CURRENT MOTORS23-13

23.19 ROUTINE TESTS23-14

23.20 HIGH-POTENTIAL TEST23-14

 23.20.1 Safety Precautions and Test Procedure23-14

 23.20.2 Test Voltage23-14

23.21 MECHANICAL VIBRATION23-14

23.22 METHOD OF MEASURING THE MOTOR VIBRATION23-14

23.23 CONDITIONS OF TEST FOR SPEED REGULATION23-14

MANUFACTURING23-14

23.24 NAMEPLATE MARKING23-14

APPLICATION DATA23-15

23.25	SERVICE CONDITIONS.....	23-15
23.25.1	General	23-15
23.25.2	Usual Service Conditions.....	23-15
23.25.3	Unusual Service Conditions.....	23-15
23.26	OPERATION OF DIRECT-CURRENT MOTORS ON RECTIFIED ALTERNATING CURRENT	23-16
23.26.1	General	23-16
23.26.2	Operation on Parallel with Power Supply with High Ripple	23-16
23.26.3	Bearing Currents.....	23-17
23.27	OPERATION OF DIRECT-CURRENT MOTORS BELOW BASE SPEED BY REDUCED ARMATURE VOLTAGE	23-17
23.28	RATE OF CHANGE OF LOAD CURRENT	23-17

Section III LARGE MACHINES

**Part 24—LARGE MACHINES—DC GENERATORS LARGER THAN 1.0 KILOWATT
PER RPM, OPEN TYPE CLASSIFICATION**

24.0	SCOPE	24-1
24.1	GENERAL INDUSTRIAL GENERATORS	24-1
24.2	METAL ROLLING MILL GENERATORS.....	24-1
24.3	REVERSING HOT MILL GENERATORS.....	24-1
	RATINGS	24-1
24.9	BASIS OF RATING.....	24-1
24.10	KILOWATT, SPEED, AND VOLTAGE RATINGS	24-2
	TESTS AND PERFORMANCE	24-3
24.40	TEMPERATURE RISE	24-3
24.40.1	Temperature Rise for Ambients Higher than 40°C	24-4
24.40.2	Temperature Rise for Altitudes Greater than 3300 Feet (1000 Meters).....	24-4
24.40.3	Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C*	24-4
24.41	OVERLOAD CAPABILITY	24-5
24.41.1	General Industrial Generators	24-5
24.41.2	Metal Rolling Mill Generators (Excluding Reversing Hot Mill Generators)—Open, Forced-Ventilated, and Totally Enclosed Water-Air-Cooled	24-5
24.41.3	Reversing Hot Mill Generators—Forced-Ventilated and Totally Enclosed Water-Air-Cooled	24-5
24.42	MOMENTARY LOAD CAPACITY.....	24-5
24.43	SUCCESSFUL COMMUTATION	24-6
24.44	OUTPUT AT REDUCED VOLTAGE.....	24-6
24.45	EFFICIENCY.....	24-6
24.46	OVERSPEED.....	24-7
24.47	FIELD DATA FOR DIRECT-CURRENT GENERATORS.....	24-7
24.48	ROUTINE TESTS	24-7
24.49	HIGH POTENTIAL TESTS	24-7
24.49.1	Safety Precautions and Test Procedure	24-7
24.49.2	Test Voltage.....	24-8
24.50	CONDITIONS OF TESTS FOR VOLTAGE REGULATION	24-8
24.51	MECHANICAL VIBRATION.....	24-8
	MANUFACTURING	24-8
24.61	NAMEPLATE MARKING	24-8
	APPLICATION DATA	24-8
24.80	SERVICE CONDITIONS.....	24-8
24.80.1	General	24-8
24.80.2	Usual Service Conditions.....	24-9
24.80.3	Unusual Service Conditions.....	24-9

24.81 RATE OF CHANGE OF LOAD CURRENT24-9

24.82 SUCCESSFUL PARALLEL OPERATION OF GENERATORS.....24-10

24.83 OPERATION OF DIRECT-CURRENT GENERATORS IN PARALLEL
WITH RECTIFIED ALTERNATING-VOLTAGE POWER SUPPLY24-10

 24.83.1 General24-10

 24.83.2 Operation in Parallel with Power Supply with Ripple.....24-10

 24.83.3 Bearing Currents.....24-10

24.84 COMPOUNDING24-11

 24.84.1 Flat Compounding24-11

 24.84.2 Other24-11

Section IV PERFORMANCE STANDARDS APPLYING TO ALL MACHINES
Part 30—APPLICATION CONSIDERATIONS FOR CONSTANT SPEED MOTORS
USED ON A SINUSOIDAL BUS WITH HARMONIC CONTENT AND
GENERAL PURPOSE MOTORS USED WITH ADJUSTABLE-VOLTAGE
OR ADJUSTABLE-FREQUENCY CONTROLS OR BOTH

30.0 SCOPE30-1

30.1 APPLICATION CONSIDERATIONS FOR CONSTANT SPEED MOTORS
USED ON A SINUSOIDAL BUS WITH HARMONIC CONTENT30-1

 30.1.1 Efficiency.....30-1

 30.1.2 Derating for Harmonic Content30-1

 30.1.3 Power Factor Correction30-2

30.2 GENERAL PURPOSE MOTORS USED WITH ADJUSTABLE-
VOLTAGE OR ADJUSTABLE-FREQUENCY CONTROLS OR BOTH.....30-2

 30.2.1 Definitions30-2

 30.2.2 Application Considerations30-5

Section IV PERFORMANCE STANDARDS APPLYING TO ALL MACHINES
Part 31—DEFINITE-PURPOSE INVERTER-FED POLYPHASE MOTORS

31.0 SCOPE31-1

31.1 SERVICE CONDITIONS.....31-1

 31.1.1 General31-1

 31.1.2 Usual Service Conditions.....31-1

 31.1.3 Unusual Service Conditions.....31-1

 31.1.4 Operation in Hazardous (Classified) Locations31-2

31.2 DIMENSIONS, TOLERANCES, AND MOUNTING FOR
FRAME DESIGNATIONS31-2

31.3 RATING31-3

 31.3.1 Basis of Rating.....31-3

 31.3.2 Base Horsepower and Speed Ratings31-3

 31.3.3 Speed Range31-4

 31.3.4 Voltage.....31-4

 31.3.5 Number of Phases31-4

 31.3.6 Direction of Rotation31-5

 31.3.7 Service Factor.....31-5

 31.3.8 Duty.....31-5

31.4 PERFORMANCE31-5

 31.4.1 Temperature Rise31-5

 31.4.2 Torque.....31-9

 31.4.3 Operating Limitations31-9

 31.4.4 Insulation Considerations31-10

 31.4.5 Resonances, Sound, Vibration31-12

 31.4.6 Bearing Lubrication at Low and High Speeds31-12

31.5 NAMEPLATE MARKING31-13

 31.5.1 Variable Torque Applications.....31-13

 31.5.2 Other Applications31-13

31.6	TESTS	31-13
	31.6.1 Test Method	31-13
	31.6.2 Routine Tests	31-14
	31.6.3 Performance Tests	31-14
31.7	ACCESSORY MOUNTING	31-14

Section IV PERFORMANCE STANDARDS APPLYING TO ALL MACHINES
Part 32—SYNCHRONOUS GENERATORS (EXCLUSIVE OF GENERATORS
COVERED BY ANSI STANDARDS C50.12, C50.13, C50.14,
AND C50.15 ABOVE 5000 KVA) RATINGS

32.0	SCOPE	32-1
32.1	BASIS OF RATING	32-1
32.2	KILOVOLT-AMPERE (KVA) AND (KW) RATINGS	32-1
32.3	SPEED RATINGS	32-1
32.4	VOLTAGE RATINGS	32-3
	32.4.1 Voltage Ratings for 60 Hz Circuits, Volts	32-3
	32.4.2 Voltage Ratings for 50 Hz Circuits, Volts	32-3
32.5	FREQUENCIES	32-3
32.6	TEMPERATURE RISE	32-3
	32.6.2 Temperature Rise for Air-Cooled Machines for Ambients Lower than 40° C, but Not Below 0° C	32-5
32.7	MAXIMUM MOMENTARY OVERLOADS	32-5
32.8	OVERLOAD CAPABILITY	32-6
32.9	OCCASIONAL EXCESS CURRENT	32-6
32.10	MAXIMUM DEVIATION FACTOR	32-6
32.11	TELEPHONE INFLUENCE FACTOR (TIF)	32-6
32.12	EFFICIENCY	32-7
32.13	SHORT-CIRCUIT REQUIREMENTS	32-8
32.14	CONTINUOUS CURRENT UNBALANCE	32-8
32.15	OPERATION WITH NON-LINEAR OR ASYMMETRIC LOADS	32-9
32.16	OVERSPEEDS	32-9
32.17	VARIATION FROM RATED VOLTAGE	32-10
	32.17.1 Broad Voltage Range	32-10
	32.17.2 Discrete Voltage	32-10
32.18	SYNCHRONOUS GENERATOR VOLTAGE REGULATION (VOLTAGE DIP)	32-10
	32.18.1 General	32-10
	32.18.2 Definitions	32-10
	32.18.3 Voltage Recorder Performance	32-12
	32.18.4 Examples	32-12
	32.18.5 Motor Starting Loads	32-12
32.19	PERFORMANCE SPECIFICATION FORMS	32-15
	32.19.1 Slip-ring Synchronous Generators	32-15
	32.19.2 Brushless Synchronous Generators	32-16
32.20	ROUTINE FACTORY TESTS	32-17
	32.20.1 Generators Not Completely Assembled in the Factory	32-17
	32.20.2 Generators Completely Assembled in the Factory	32-17
32.21	HIGH-POTENTIAL TESTS	32-17
	32.21.1 Safety Precautions and Test Procedures	32-17
	32.21.2 Test Voltage—Armature Windings	32-17
	32.21.3 Test Voltage—Field Windings, Generators with Slip Rings	32-17
	32.21.4 Test Voltage—Assembled Brushless Generator Field Winding and Exciter Armature Winding	32-17
	32.21.5 Test Voltage—Brushless Exciter Field Winding	32-18
32.22	MACHINE SOUND SYNCHRONOUS (GENERATORS)	32-18
	32.22.1 Sound Quality	32-18

32.22.2	Sound Measurement	32-18
32.23	VIBRATION.....	32-18
	MANUFACTURING DATA	32-19
32.24	NAMEPLATE MARKING	32-19
32.25	SHAFT EXTENSION KEY	32-19
32.26	GENERATOR TERMINAL HOUSING	32-19
32.27	EMBEDDED TEMPERATURE DETECTORS	32-20
	APPLICATION DATA	32-21
32.29	PARALLEL OPERATION	32-21
32.30	CALCULATION OF NATURAL FREQUENCY	32-21
32.31	TORSIONAL VIBRATION.....	32-21
32.32	MACHINES OPERATING ON AN UNGROUNDED SYSTEM	32-21
32.33	SERVICE CONDITIONS.....	32-21
32.33.1	General	32-21
32.33.2	Usual Service Conditions.....	32-22
32.33.3	Unusual Service Conditions.....	32-22
32.34	NEUTRAL GROUNDING.....	32-23
32.35	STAND-BY GENERATOR.....	32-23
32.36	GROUNDING MEANS FOR FIELD WIRING	32-23

Section IV PERFORMANCE STANDARDS APPLYING TO ALL MACHINES

Part 33—DEFINITE PURPOSE SYNCHRONOUS GENERATORS FOR GENERATING SET APPLICATIONS

33.0	SCOPE	33-1
33.1	DEFINITIONS	33-1
33.1.1	Rated Output Power	33-1
33.1.2	Rated Speed of Rotation n	33-2
33.1.3	Voltage Terms.....	33-2
33.1.4	Performance Classes	33-4
33.2	RATINGS	33-5
33.2.1	Power Factor.....	33-5
33.2.2	Kilovolt – Ampere (kVA) and Kilowatt (kW) Ratings	33-5
33.2.3	Speed.....	33-6
33.2.4	Voltage.....	33-6
33.2.5	Frequencies	33-7
33.3	PERFORMANCE	33-7
33.3.1	Voltage and Frequency Variation	33-7
33.3.2	Limits of Temperature and Temperature Rise	33-8
33.3.3	Special Load Conditions	33-11
33.3.4	Power Quality.....	33-12
33.3.5	Overspeed	33-18
33.3.6	Machine Sound.....	33-18
33.3.7	Linear Vibration.....	33-19
33.3.8	Testing	33-19
33.3.9	Performance Specification Forms.....	33-22
33.4	APPLICATIONS.....	33-24
33.4.1	Service Conditions.....	33-24
33.4.2	Transient Voltage Performance	33-25
33.4.3	Torsional Vibration	33-29
33.4.4	Generator Grounding.....	33-29
33.4.5	Cyclic Irregularity	33-30
33.4.6	Application Criteria.....	33-30
33.5	MANUFACTURING	33-32
33.5.1	Nameplate Marking.....	33-32
33.5.2	Terminal Housings.....	33-33

Foreword

The standards appearing in this publication have been developed by the Motor and Generator Section and approved for publication as Standards of the National Electrical Manufacturers Association. They are intended to assist users in the proper selection and application of motors and generators. These standards are revised periodically to provide for changes in user needs, advances in technology, and changing economic trends. All persons having experience in the selection, use, or manufacture of electric motors and generators are encouraged to submit recommendations that will improve the usefulness of these standards. Inquiries, comments, and proposed or recommended revisions should be submitted to the Motor and Generator Section by contacting:

Vice President, Technical Services
National Electrical Manufacturers Association
1300 North 17th Street, Suite 1752
Rosslyn, VA 22209

The best judgment of the Motor and Generator Section on the performance and construction of motors and generators is represented in these standards. They are based upon sound engineering principles, research, and records of test and field experience. Also involved is an appreciation of the problems of manufacture, installation, and use derived from consultation with and information obtained from manufacturers, users, inspection authorities, and others having specialized experience. For machines intended for general applications, information as to user needs was determined by the individual companies through normal commercial contact with users. For some motors intended for definite applications, the organizations that participated in the development of the standards are listed at the beginning of those definite-purpose motor standards.

Practical information concerning performance, safety, test, construction, and manufacture of alternating-current and direct-current motors and generators within the product scopes defined in the applicable section or sections of this publication is provided in these standards. Although some definite-purpose motors and generators are included, the standards do not apply to machines such as generators and traction motors for railroads, motors for mining locomotives, arc-welding generators, automotive accessory and toy motors and generators, machines mounted on airborne craft, etc.

In the preparation and revision of these standards, consideration has been given to the work of other organizations whose standards are in any way related to motors and generators. Credit is hereby given to all those whose standards may have been helpful in the preparation of this volume.

NEMA Standards Publication No. MG 1-2009, Revision 1-2010 revises and supersedes the NEMA Standards Publication No. MG 1-2009. Prior to publication, the NEMA Standards and Authorized Engineering Information that appear in this publication unchanged since the preceding edition were reaffirmed by the Motor and Generator Section.

The standards or guidelines presented in a NEMA Standards Publication are considered technically sound at the time they are approved for publication. They are not a substitute for a product seller's or user's own judgment with respect to the particular product referenced in the standard or guideline, and NEMA does not undertake to guaranty the performance of any individual manufacturer's products by virtue of this standard or guide. Thus, NEMA expressly disclaims any responsibility for damages arising from the use, application, or reliance by others on the information contained in these standards or guidelines.